

1 LOCATION OF WATER WELL: County: Johnson		Fraction SW ¼ NW ¼ NW ¼	Section Number 24	Township Number T 13 S	Range Number R 21 E/W
Distance and direction from nearest town or city street address of well if located within city? 2 MILES SW OF DeSoto, KS					
2 WATER WELL OWNER: U.S. Army Sunflower Army Ammunition Plant RR#, St. Address, Box # : P.O. Box 640, 35425 W. 103rd St. City, State, ZIP Code : DeSoto, KS 66018			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N W E SW SE S		4 DEPTH OF COMPLETED WELL 12.52 ft. ELEVATION: 855.10 Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 11.96 ft. below land surface measured on mo/day/yr 12-01-94 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter. 10 in. to 12.3 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only (10) Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No..... X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes (No)			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) (2) PVC 4 ABS Blank casing diameter 2 in. to 7 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface 28.08 in., weight 0.70 lbs./ft. Wall thickness or gauge No. SCH 40		CASING JOINTS: Glued Clamped Welded Threaded. X TYPE OF SCREEN OR PERFORATION MATERIAL: (7) PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot (3) Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 7.14 ft. to 12.18 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 5.0 ft. to 12.3 ft., From ft. to ft. From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 4 ft., From 4 ft. to 7 ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage (16) Other (specify below) 13 Insecticide storage SWMU 22 Direction from well? How many feet?					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0	9	CLAYEY SANDY SILT			
9	10	SILTY CLAYEY SAND			
10	11	CLAYEY SILT			
11	11.5	SANDY SILTY CLAY			
11.5	12.3	LIMESTONE			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-30-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 102 This Water Well Record was completed on (mo/day/yr) 2-27-96 under the business name of LAYNE, INC. by (signature) _____					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					