

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: DOUGLAS	NW 1/4 NW 1/4 SW 1/4	29	T 13 S	R 21 E/W

Distance and direction from nearest town or city street address of well if located within city?  
 2 1/2 miles south, 1 west of Eudora

2 WATER WELL OWNER: Selah Ibrahim  
 RR#, St. Address, Box #: P.O. Box 881 Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Lawrence, KS 66044 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 100 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. 14' ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 6' ft. below land surface measured on mo/day/yr 12/17/98

Pump test data: Well water was ft. after hours pumping gpm  
 Est. Yield 1 1/2 gpm: Well water was ft. after hours pumping gpm  
 Bore Hole Diameter 8 3/4 in. to ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		9 Dewatering
		10 Monitoring well
		12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes.....No...X.....; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
		7 Fiberglass		Threaded

Blank casing diameter 5" in. to 0-12 ft., Dia 5" in. to 22-82 ft., Dia in. to ft.  
 Casing height above land surface 24" in., weight 2.85 lbs./ft. Wall thickness or gauge No. 258

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 12 ft. to 22 ft., From ft. to ft.  
 From 82 ft. to 100 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 12 ft. to 100 ft., From ft. to ft.  
 From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 12 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? SE How many feet? 250'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top Soil			
2	10	Clay-Brown			
10	12	Sandstone-Brown			
12	16	Limestone-Grey			
16	22	Shale-Grey			
22	38	Limestone-Grey			
38	44	Shale-Black			
44	52	Limestone-Grey			
52	66	Shale-Grey			
66	85	Limestone-Grey			
85	124	Shale-Grey			
124	169	Limestone-Grey			
169	200	Shale-Grey			

NOTE: 12/29/98 Permission to shallow grout from Rich Harper

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/17/98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 12-4-99 under the business name of STRADER DRILLING CO., INC. by (signature) [Signature]

OFFICE USE ONLY  
T  
R  
EW  
SEC.