

Form 3-3

WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No.

045MW004

1 LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 SE 1/4 Section Number 12 Township Number T 13 S Range Number R 21 EW		
City: JOHNSON Distance and direction from nearest town or city street address of well if located within city? 045MW004 @ SUNFLOWER ARMY AMMUNITION PLANT NEAR DESOTO, KS		
2 WATER WELL OWNER: US ARMY CORPS OF ENGINEERS RR#, St. Address, Box #: 601 E. 12TH STREET City, State, ZIP Code: KANSAS CITY, MO 64104 Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 25.7 ft. ELEVATION:	
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter: 6. 3/8 in. to 25.7 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes. No. ☒ If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No ☒	
	5 TYPE OF BLANK CASING USED:	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued. Clamped.
	1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded	2 PVC 4 ABS 7 Fiberglass Threaded. ☒
	Blank casing diameter 2 in. to 10.0 ft., Dia in. to ft., Dia in. to ft.	Casing height above land surface. 34.8 in., weight lbs./ft. Wall thickness or gauge No. <u>SCHEDULE 40</u>
TYPE OF SCREEN OR PERFORATION MATERIAL:		
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement	2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)	
SCREEN OR PERFORATION OPENINGS ARE:		
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)	2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes	
REEN-PERFORATED INTERVALS: From 10.0 ft. to 25.0 ft., From ft. to ft.		
GRAVEL PACK INTERVALS: From 7.8 ft. to 25.7 ft., From ft. to ft.		
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		
Grout intervals: From 0 ft. to 4.8 ft., From ft. to ft., From ft. to ft.		
What is the nearest source of possible contamination:		
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well	2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)	13 Insecticide storage <u>ABANDONED MUNITIONS FACILITY</u>	
Direction from well? How many feet?		
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS		
0 7 BROWN SILTY CLAY		
7 15 BROWN SANDY CLAY		
15 23 BROWN SILTY CLAY		
23 25.7 BROWN SHALEY CLAY		
25.7 BROWN SHALE		
RECEIVED DEC 09 2004 BUREAU OF WATER		
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3/27/03</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. <u>704</u> This Water Well Record was completed on (mo/day/yr) <u>3/27/03</u> under the business name of <u>Maxs</u> by (signature) <u>David H. Hargis</u>		

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.