


1 LOCATION OF WATER WELL:		Fraction	Section Number		Township Number	Range Number
County: JOHNSON		SW 1/4 SE 1/4 NW 1/4	29		T 13 S	R 22 EW
Distance and direction from nearest town or city street address of well if located within city? 2 MILES SW OF DESOTO, KS						
2 WATER WELL OWNER: US ARMY SUNFLOWER ARMY AMMUNITION PLANT						
RR#, St. Address, Box #: PO BOX 640, 35425 W 103rd ST						
City, State, ZIP Code: DE SOTO, KS 66018						
Board of Agriculture, Division of Water Resources Application Number:						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 10.16 ft. ELEVATION: 907.99				
		Depth(s) Groundwater Encountered 1. DRY ft. 2. ft. 3. ft.				
		WELL'S STATIC WATER LEVEL DRY ft. below land surface measured on mo/day/yr				
		Pump test data: Well water was ft. after hours pumping gpm				
		Est. Yield gpm: Well water was ft. after hours pumping gpm				
		Bore Hole Diameter 10 in. to 16.7 ft. and in. to ft.				
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well				
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)				
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well				
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted				
		Water Well Disinfected? Yes No				
5 TYPE OF BLANK CASING USED:						
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped						
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded						
Blank casing diameter 2 in. to 12 ft. Dia in. to ft. Dia in. to ft.						
Casing height above land surface 27.36 in. weight 0.70 lbs./ft. Wall thickness or gauge No. SCH. 40						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement						
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)						
12 None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)						
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes						
7 Torch cut 10 Other (specify)						
SCREEN-PERFORATED INTERVALS: From 5.59 ft. to 10.0 ft. From ft. to ft.						
GRAVEL PACK INTERVALS: From 3.0 ft. to 10.2 ft. From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout Intervals: From 0 ft. to 5 ft. From 5 ft. to 8.8 ft. From ft. to ft.						
What is the nearest source of possible contamination:						
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well						
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well						
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)						
13 Insecticide storage BACKGROUND						
Direction from well? How many feet?						
FROM TO		LITHOLOGIC LOG		FROM TO		PLUGGING INTERVALS
0 13.5		CLAYEY SILT				
13.5 15		HIGHLY WEATHERED LIMESTONE				
15 16.7		WEATHERED LIMESTONE w/ CLAYEY SILT				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-9-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 102 This Water Well Record was completed on (mo/day/yr) 3-4-96 under the business name of LAYNE, INC. by (signature) [Signature]						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						