WATER WELL F	ECORD Form WWC-	5 KSA 82a-121	12 MW	81-56
LOCATION OF WATER WELL: Fraction		ction Number	Township Number	· · · · · · · · · · · · · · · · · · ·
ounty: Tohnson NW 14 SE	1/4 MM 1/4	20	т <b>/3</b> s	S   R 23 (E)W
stance and direction from nearest town or city street address of	well it located within city?			
WATER WELL OWNER // 5 / 2/14/EA/	7 1	• _		
WATER WELL OWNER: W.S. GOVERNMEN R#, St. Address, Box # : SUNFLOWER SRM	Y Ammuni	TION PL	Noard of Agricult	ture. Division of Water Resource
ty, State, ZIP Code : DESOTO, KANSAS	•		Application Num	ber: , ,
LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETE	D WELL 32.2.	ft ELEVATIO		
AN "X" IN SECTION BOX: Depth(s) Groundwater Enc			T ,	ft. 3. Upad
WELL'S STATIC WATER I	EVEL 24.57 ft.	pelow land surface	measured on mo/d	av/vr 11-24-81
				rs pumping gpn
I NWI_ Nt I				rs pumping gpn
1 1 1 1 1 1 2 2				in. to
W I I WELL WATER TO BE US	· · · · · · · · · · · · · · · · · · ·	=	Air conditioning	11 Injection well
1 Domestic 3 F	eedlot 6 Oil field wa	ater supply 9 [	Dewatering	12 Other (Specify below)
2 Irrigation 4 Ir	ndustrial 7 Lawn and	garden only	Observation well	Mondoring Wel
Was a chemical/bacteriolog	ical sample submitted to D	epartment? Yes	No	lf yes, mo/day/yr sample was su
\$ mitted		Water \	Well Disinfected? Ye	es (No)
TYPE OF BLANK CASING USED: 5 Wroug	ht iron 8 Conc	rete tile .	CASING JOINTS:	Glued Clamped
1 Steel 3 RMP (SR) 6 Asbes	tos-Cement 9 Other	(specify below)		Welded
2 PVP 4 ABS 7 Fiberg				Threaded
				in. to f
asing height above land surface	ıt	lbs./ft. V	Vall thickness or gau	ige No. <i>5ch</i> <b>4</b> 0
YPE OF SCREEN OR PERFORATION MATERIAL:	(7 P)		10 Asbestos	cement
1 Steel 3 Stainless steel 5 Fiberg	lass 8 Ri	MP (SR)	11 Other (sp	ecify)
2 Brass 4 Galvanized steel 6 Concre	ete tile 9 Al	3S	12 None use	d (open hole)
CREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8	Saw cut	11 None (open hole)
1 Continuous slot 3 Mill slop	6 Wire wrapped	_	Drilled holes	
2 Louvered shutter 4 Key punched	7 Torch cut			
CREEN-PERFORATED INTERVALS: From				. ft. tof
From				. ft. to
	ft. to 32. 2.			. ft. tof
From 0.00	ft. to	ft., From	er Neat Cer	ment W/ 19
GROUT MATERIAL:  1 Neat cement 2 Cement 3 crowt Intervals: From. O.C ft. to	grout 3 Bent From ft.	onite 40th	" En Bento	nite "
/hat is the nearest source of possible contamination:	FIORI	10 Livestock		14 Abandoned water well
·	Pit privy	11 Fuel stor	•	15 Oil well/Gas well
and the control of th	Sewage lagoon	12 Fertilizer	•	16 Other (specify below)
the contract of the contract o	Feedyard	13 Insecticid	•	
Direction from well?	recayara	How many f	•	
FROM TO LITHOLOGIC LOG	FROM	ТО		DLOGIC LOG
,0' 2.0' CLAY				
O' 5,5' CLAYEY SILT				
5' 7.3' V1/25 54 FM	. ,			
3' 21.5' Spring Hill LS MBA	C-Platts bu	9 LS F	M	
15' 32,2 Bonner Springs Sh	FM			
		<del>                                     </del>	7.657-77	
	#	<u> </u>		
		<b> </b>		
		1		**************************************
		$\bot$		
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION; This	water well was (1) constr	ucted) (2) reconstr	ructed, or (3) plugge	d under my jurisdiction and wa
ompleted on (mo/day/year)		and this record is	s true to the best of r	my knowledge and belief. Kansa
	his Water Well Record w			C. 18, 1981
nder the business name of 2/5. Army Caro	OF ENGINEE	PS by (signature	hw	Marken
ISTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS	FIRMLY and PRINT clea	rly. Please fill ip of	anks, underline or cir	cle the correct answers. Send to
ree copies to Kansas Department of Health and Environment, Divisi	on of Environment, Enviror	nmental Geol <b>éay-8</b>	ection, Topeka, KS 6	6620. Send one to WATER WEL