

MW6

WATER WELL RECORD

Form WWC-5

Division of Water Resources App. No.

1 LOCATION OF WATER WELL: Fraction SE SE SE Section Number 25 Township No. T 13 S Range Number R25 E W
 County: Johnson
 Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here
Deels Mini-Mart
1100 E. Santa Fe; Olathe, Ks.

2 WATER WELL OWNER: Sundeep, LLC
 RR#, Street Address, Box #: 15625 S. Moonlight Rd.
 City, State, ZIP Code: Olathe, Ks. 66061

3 LOCATE WELL WITH AN "X" IN SECTION BOX:
 N
 W | | E
 --NW-- --NE--
 | |
 --SW-- --SE--
 | |
 S
 [-----] mile [-----]

4 DEPTH OF COMPLETED WELL 17' ft.
 Depth(s) Groundwater Encountered (1).....ft. (2).....ft. (3).....ft.
 WELL'S STATIC WATER LEVEL 15.09' ft. below land surface measured on mo/day/yr. 4/30/14
 Pump test data: Well water was.....ft. after..... hours pumping..... gpm
 EST. YIELD.....gpm Well water was.....ft. after..... hours pumping..... gpm
 Bore Hole Diameter 7.5 in. to 17' ft., andin. toft.
 WELL WATER TO BE USED AS: Public water supply Geothermal Injection well
 Domestic Feedlot Oil field water supply Dewatering Other (Specify below)
 Irrigation Industrial Domestic-lawn & garden Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No
 If yes, mo/day/yr sample was submitted.....
 Water well disinfected? Yes No

5 TYPE OF CASING USED: Steel PVC Other
 CASING JOINTS: Glued Clamped Welded Threaded
 Casing diameter 2.375 in. to 4' ft., Diameter in. to ft., Diameter in. to ft.
 Casing height above land surface Flush in., Weight lbs./ft., Wall thickness or gauge No. 3/4
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 Steel Stainless Steel PVC Other (Specify)
 Brass Galvanized Steel None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)
 Louvered shutter Key punched Wire wrapped Saw cut Other (specify)
 SCREEN-PERFORATED INTERVALS: From.....17' ft. to 4' ft., From ft. to ft.
 From..... ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From.....17' ft. to 3' ft., From ft. to ft.
 From..... ft. to ft., From ft. to ft.

6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other concrete
 Grout Intervals: From.....3' ft. to 15' ft., From.....15' ft. to 6' ft., From ft. to ft.
 What is the nearest source of possible contamination:
 Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)
 Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well
 Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well
 Direction from well East South East Distance from well 70'

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHO. LOG (cont.) or PLUGGING INTERVALS
0	1.50	Concrete			
1.50	4.0	DK. Bin to Black clay			
4.0	9.0	Blue Green High mottled clay			
9.0	14.0	Bin clay w/ iron oxides			
14.0	16.90	Reddish weathered shale			
16.90	17.0	limestone			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 4/15/14 and this record is true to the best of my knowledge and belief.
 Kansas Water Well Contractor's License No. 132 This Water Well Record was completed on (mo/day/year) 4/30/14
 under the business name of G.B. Environmental Dilling by (signature) James Biebel

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send one copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at <http://www.kdheks.gov/waterwell/index.html>