

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Johnson</u>	<u>SE</u> $\frac{1}{4}$ <u>NW</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$	<u>35</u>	T <u>13</u> S	R <u>23</u> <u>EW</u>

Distance and direction from nearest town or city street address of well if located within city?

203 S. Kansas, Olathe, Ks. 66061

2 WATER WELL OWNER: Robert Hunt	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 616 S. Harrison	Application Number:
City, State, ZIP Code: Olathe, Ks. 66061	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>19'</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. <u>15'</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>5.0</u> ft. below land surface measured on mo/day/yr <u>4-10-95</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>8 1/2"</u> in. to <u>19'</u> ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10</u> Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No <u>X</u>; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>No</u>

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
<u>2 PVC</u>	7 Fiberglass		Threaded. <u>X</u>
Blank casing diameter <u>2.375</u> in. to <u>8'9"</u> ft., Dia			in. to SDR <u>13</u> ft.
Casing height above land surface <u>4' Flush Mount</u> in., weight			lbs./ft. Wall thickness or gauge No. <u>SCH 40</u>
TYPE OF SCREEN OR PERFORATION MATERIAL:	<u>7 PVC</u>	10 Asbestos-cement	
1 Steel	8 RMP (SR)	11 Other (specify)	
2 Brass	9 ABS	12 None used (open hole)	
3 Stainless steel			
4 Galvanized steel			
5 Fiberglass			
6 Concrete tile			
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS: From <u>19'</u> ft. to <u>9'</u> ft., From ft. to ft.			
From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From <u>19'</u> ft. to <u>7'</u> ft., From ft. to ft.			
From ft. to ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From <u>7'</u> ft. to <u>3'</u> ft., From <u>3'</u> ft. to <u>0'</u> ft., From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	11 Fuel storage <u>Former</u>	15 Oil well/Gas well		
2 Sewer lines	12 Fertilizer storage	16 Other (specify below)		
3 Watertight sewer lines	13 Insecticide storage			
4 Lateral lines				
5 Cess pool				
6 Seepage pit				
7 Pit privy				
8 Sewage lagoon				
9 Feedyard				
Direction from well? <u>In Old Tank Pch</u>	How many feet? <u>0</u>			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Ls. Rx. Gravel			
1	9	Dk gray-dk green mottled silty clay fill, strong odor, moist, iron oxides staining.			
9	11	Gray brn clay, iron oxides, slight olive clay mottling, faint odor.			
11	15	Tan gray brn mottled clay, iron oxides, moist, no odor, (weathered shales)			
15	19	Wet at 15' Gray olive shale, dry to moist, firm, odor, lx.rx.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3-25-95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>539</u> This Water Well Record was completed on (mo/day/yr) <u>4-11-95</u> under the business name of <u>JB Environmental Drilling</u> by (signature) <u>James Baker</u>
--