

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Johnson		SE ¼ NW ¼ NE ¼	35	T 13 S	R 23 EW
Distance and direction from nearest town or city street address of well if located within city? 203 S. Kansas, Olathe, Ks. 66061					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources Application Number:			
RR#, St. Address, Box # City, State, ZIP Code		Robert Hunt 616 S. Harrison Olathe, Ks. 66061			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL. 18'6" ft. ELEVATION:			
Diagram: A square divided into four smaller squares labeled NW, NE, SW, and SE. An 'X' is marked in the center of the NE square. To the left of the diagram is a vertical arrow pointing up, labeled 'N'. To the right is a horizontal arrow pointing right, labeled 'E'. Below the diagram is a horizontal arrow pointing left, labeled 'W'. To the far left is a vertical double-headed arrow labeled '1 Mile'.		Depth(s) Groundwater Encountered 1. 10' ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 10.40 ... ft. below land surface measured on mo/day/yr 4-10-95			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm; Well water was ft. after hours pumping gpm			
		Bore Hole Diameter... 8 1/2" in. to 18'6" ft., and in. to ft.			
		WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only (10) Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
(2) PVC		4 ABS		8 Concrete tile	
Blank casing diameter 2.375 in. to 8'3" ft., Dia.		6 Asbestos-Cement		9 Other (specify below)	
Casing height above land surface Flush Mount , weight		7 Fiberglass		CASING JOINTS: Glued Clamped	
TYPE OF SCREEN OR PERFORATION MATERIAL:		8 RMP (SR)		Welded Threaded X	
1 Steel		9 ABS		SDR 13	
2 Brass		10 Asbestos-cement		SCH 40	
3 Stainless steel		11 Other (specify)			
4 Galvanized steel		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		8 Saw cut	
1 Continuous slot		6 Wire wrapped		11 None (open hole)	
(3) Mill slot		7 Torch cut		9 Drilled holes	
2 Louvered shutter		10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From 18'6" ft. to 8'6" ft., From ft. to ft.			
		From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS:		From 18'6" ft. to 7' ft., From ft. to ft.			
		From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL:					
Grout Intervals: From 7' ft. to 3' ft., From 3' ft. to 0 ft., From ft. to ft.		1 Neat cement		2 Cement grout	
What is the nearest source of possible contamination:		3 Bentonite		4 Other	
1 Septic tank		7 Pit privy		10 Livestock pens	
2 Sewer lines		8 Sewage lagoon		11 Fuel storage Fouler	
3 Watertight sewer lines		9 Feedyard		12 Fertilizer storage	
4 Lateral lines				13 Insecticide storage	
5 Cess pool				14 Abandoned water well	
6 Seepage pit				15 Oil well/Gas well	
				16 Other (specify below)	
Direction from well? went		How many feet? 50'			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Asphalt/Cement			
1	3.50	Dk gray clay, moist, no odor, firm.			
3.50	14	Gray brn to brn clay, mottled w/ iron oxides & gray clay, moist, firm.			
14	18	Olive gray shale, dry to moist, no odor, friable.			
18	18'6"	Limestone, rust color.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-25-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 . This Water Well Record was completed on (mo/day/yr) 4-11-95 under the business name of JB Environmental Drilling by (signature) James Bieber					