

1) LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Johnson		SW ¼ NW ¼ SE ¼	30	T 13 S	R 24 EW
Distance and direction from nearest town or city street address of well if located within city?					
400 North Rogers Road, Olathe, KS					
2) WATER WELL OWNER: AlliedSignal		MW-2	Board of Agriculture, Division of Water Resources		
RR#, St. Address, Box # : 400 North Rogers Road		Application Number:			
City, State, ZIP Code : Olathe, KS 66062					
3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4) DEPTH OF COMPLETED WELL: 18.5 ft. ELEVATION:			
N ---NW---NE--- W---XSW---SE---E S 1 Mile ↑ ↓		Depth(s) Groundwater Encountered 1. Dry ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 10.19 ft. below land surface measured on mo/day/yr 3/22/96			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
Bore Hole Diameter 6 in. to ft., and in. to ft.		WELL WATER TO BE USED AS:			
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		5 Public water supply 8 Air conditioning 11 Injection well			
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes No X			
5) TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped Welded Threaded X			
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)					
2 PVC 4 ABS 7 Fiberglass					
Blank casing diameter 1 in. to 10.0 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 0.0 in., weight 0.70 lbs./ft. Wall thickness or gauge No. sch 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 18.5 ft. to 10 ft., From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 10 ft. to 6 ft., From ft. to ft., From ft. to ft.					
6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 6 ft. to 1 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Industrial					
Direction from well? south west How many feet? 100					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	DK BROWN SILTY CLAY Firm-STIFF			
4	8	Red Brown SILTY CLAY, STIFF			
8	12	SHALE, sandy, STIFF, DAMP			
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 3/21/96 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 602 This Water Well Record was completed on (mo/day/yr) 4/10/96					
under the business name of Hydro-LOGIC, Inc. by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					