


Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction	WATER WELL RECORD		Section Number	Township Number	Range Number	
County: Johnson		SW 1/4	NE 1/4	NW 1/4	9	T 13 S	R 24 E	EXX
Distance and direction from nearest town or city street address of well if located within city?								
14600 West 106th Street, Lenexa, KS/South parking lot								
2 WATER WELL OWNER: Deluxe Corporation								
RR#, St. Address, Box #: P.O. Box 64399						Board of Agriculture, Division of Water Resources		
City, State, ZIP Code: St. Paul, MN 55164						Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 13 ft. ELEVATION: 1034.46						
		Depth(s) Groundwater Encountered 1. NA ft. 2. ft. 3. ft.						
		WELL'S STATIC WATER LEVEL NA ft. below land surface measured on mo/day/yr						
		Pump test data: Well water was ft. after hours pumping gpm						
		Est. Yield gpm: Well water was ft. after hours pumping gpm						
		Bore Hole Diameter 6.0 in. to 13 ft., and in. to						
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well						
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)						
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well MW 3/St 3						
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted						
		Water Well Disinfected? Yes No X						
5 TYPE OF BLANK CASING USED:								
1 Steel			3 RMP (SR)			5 Wrought iron		
2 PVC			4 ABS			6 Asbestos-Cement		
						7 Fiberglass		
Blank casing diameter 2 in. to 3 ft.			Dia in. to ft.			CASING JOINTS: Glued Clamped		
Casing height above land surface 0 in.			weight lbs./ft.			Wall thickness or gauge No. Sch. 40		
TYPE OF SCREEN OR PERFORATION MATERIAL:								
1 Steel			3 Stainless steel			5 Fiberglass		
2 Brass			4 Galvanized steel			6 Concrete tile		
SCREEN OR PERFORATION OPENINGS ARE:			5 Gauzed wrapped			8 Saw cut		
1 Continuous slot			3 Mill slot			6 Wire wrapped		
2 Louvered shutter			4 Key punched			7 Torch cut		
SCREEN-PERFORATED INTERVALS:			From 3 ft. to 13 ft.			From ft. to ft.		
GRAVEL PACK INTERVALS:			From ft. to ft.			From ft. to ft.		
6 GROUT MATERIAL:								
1 Neat cement			2 Cement grout			3 Bentonite		
Grout Intervals: From 0 ft. to 2 ft.			From ft. to ft.			From ft. to ft.		
What is the nearest source of possible contamination:								
1 Septic tank			4 Lateral lines			7 Pit privy		
2 Sewer lines			5 Cess pool			8 Sewage lagoon		
3 Watertight sewer lines			6 Seepage pit			9 Feedyard		
Direction from well?			How many feet?					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS								
0 5 SP Sand Fill								
5 7 SP Sandy Med Gr. Fill								
7 13 Limestone								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/9/97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 549 This Water Well Record was completed on (mo/day/yr) 7/24/97 under the business name of J & R Drilling Services by signature Raymond Rouns								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records								