

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number												
County: <u>Johnson</u>		NE 1/4 NE 1/4 NE 1/4	1	T 13 S	R 24 <u>EW</u>												
Distance and direction from nearest town or city street address of well if located within city? <u>9001 West 95th Street</u>																	
2 WATER WELL OWNER: <u>Texaco Refining and Marketing, Inc.</u>																	
RR#, St. Address, Box # :		P.O. Box 1650		Board of Agriculture, Division of Water Resources													
City, State, ZIP Code :		Tulsa, Oklahoma 74102		Application Number:													
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>25.5</u> ft. ELEVATION: <u>22.0</u> ft.															
N 1 Mile W E S <table border="1" style="margin: auto; text-align: center;"><tr><td> </td><td> </td><td> </td><td>X</td></tr><tr><td>NW</td><td> </td><td>NE</td><td> </td></tr><tr><td>SW</td><td> </td><td>SE</td><td> </td></tr></table>					X	NW		NE		SW		SE		Depth(s) Groundwater Encountered 1. <u>22.0</u> ft. 2. <u> </u> ft. 3. <u> </u> ft.			
					X												
		NW		NE													
		SW		SE													
		WELL'S STATIC WATER LEVEL <u>12.7</u> ft. below land surface measured on mo/day/yr															
Pump test data: Well water was <u> </u> ft. after <u> </u> hours pumping <u> </u> gpm																	
Est. Yield <u> </u> gpm: Well water was <u> </u> ft. after <u> </u> hours pumping <u> </u> gpm																	
Bore Hole Diameter <u>7.75</u> in. to <u>25.5</u> ft. and <u> </u> in. to <u> </u> ft.																	
WELL WATER TO BE USED AS:				5 Public water supply 8 Air conditioning 11 Injection well													
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)																	
2 Irrigation 4 Industrial 7 Lawn and garden only <u>10</u> Monitoring well																	
Was a chemical/bacteriological sample submitted to Department? Yes <u> </u> No <u>X</u> ; If yes, mo/day/yr sample was submitted				Water Well Disinfected? Yes <u> </u> No <u> </u>													
5 TYPE OF BLANK CASING USED:																	
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u> </u> Clamped <u> </u>												
<u>2</u> PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded <u> </u>												
			7 Fiberglass		Threaded <u> </u>												
Blank casing diameter <u>4</u> in. to <u>5.0</u> ft. Dia <u> </u> in. to <u> </u> ft. Dia <u> </u> in. to <u> </u> ft.																	
Casing height above land surface <u>-0.3</u> in. weight <u> </u> lbs./ft. Wall thickness or gauge No. <u> </u>																	
TYPE OF SCREEN OR PERFORATION MATERIAL:																	
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement												
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify) <u> </u>												
					12 None used (open hole)												
SCREEN OR PERFORATION OPENINGS ARE:																	
1 Continuous slot		<u>2</u> Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)												
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes													
			7 Torch cut	10 Other (specify) <u> </u>													
SCREEN-PERFORATED INTERVALS: From <u>5.0</u> ft. to <u>25.0</u> ft. From <u> </u> ft. to <u> </u> ft.																	
GRAVEL PACK INTERVALS: From <u>4.0</u> ft. to <u>25.5</u> ft. From <u> </u> ft. to <u> </u> ft.																	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite <u>4</u> Other <u>Pre-Mix/Bentonite</u>																	
Grout Intervals: From <u>0</u> ft. to <u>2.0</u> ft. From <u> </u> ft. to <u> </u> ft.																	
What is the nearest source of possible contamination:																	
1 Septic tank		4 Lateral lines	7 Pit privy	<u>10</u> Livestock pens	14 Abandoned water well												
2 Sewer lines		5 Cess pool	8 Sewage lagoon	<u>11</u> Fuel storage	15 Oil well/Gas well												
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)												
Direction from well? <u>Southwest</u>		How many feet? <u> </u>															
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS												
0	22	Silty clay															
22	26	Shale; Gray, soft, fissile															
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, <u>(2)</u> reconstructed, or <u>(3)</u> plugged under my jurisdiction and was completed on (mo/day/year) <u>1-28-92</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>529</u> This Water Well Record was completed on (mo/day/yr) <u>2-26-92</u> under the business name of <u>Geotechnology, Inc.</u> by (signature) <u>AT Baldem</u>																	
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																	