

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Johnson		SE 1/4 SW 1/4 SW 1/4	30	T 13 S	R 24 W
Distance and direction from nearest town or city street address of well if located within city? Property immediately east of Texaco station, 1800 Santa Fe, Olathe					
2 WATER WELL OWNER: Texaco Refining & Marketing Inc.					
RR#, St. Address, Box #: 1437 S. Boulder			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code: Tulsa, OK 74119			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 10 ft. ELEVATION: 90.99'			
		Depth(s) Groundwater Encountered 1. 5.65 ft. 2. _____ ft. 3. _____ ft.			
		WELL'S STATIC WATER LEVEL 4.80 ft. below land surface measured on mo/day/yr 5/1/91			
		Pump test data: Well water was _____ ft. after _____ hours pumping _____ gpm			
		Est. Yield _____ gpm: Well water was _____ ft. after _____ hours pumping _____ gpm			
		Bore Hole Diameter 7.25 in. to 10 ft. and _____ in. to _____ ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes _____ No ☒ If yes, mo/day/yr sample was submitted _____			
		Water Well Disinfected? Yes _____ No ☒			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued _____ Clamped _____
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded _____
			7 Fiberglass		Threaded ☒
Blank casing diameter 4 in. to 2 ft., Dia _____ in. to _____ ft., Dia _____ in. to _____ ft.					
Casing height above land surface Ground Level in., weight _____ lbs./ft. Wall thickness or gauge No. Sch. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify) _____
					12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify) _____	
SCREEN-PERFORATED INTERVALS:					
From 2 ft. to 10 ft.		From _____ ft. to _____ ft.			
From _____ ft. to _____ ft.		From _____ ft. to _____ ft.			
GRAVEL PACK INTERVALS:					
From 1.5 ft. to 10 ft.		From _____ ft. to _____ ft.			
From _____ ft. to _____ ft.		From _____ ft. to _____ ft.			
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout	3 Bentonite	4 Other _____	
Grout Intervals: From 0.5 ft. to 1.5 ft.		From 0 ft. to 0.5 ft.			
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	11 Fuel storage	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	13 Insecticide storage	16 Other (specify below) _____
Direction from well? NW		How many feet? ~150			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8'	Varicolored, silty to fine sandy CLAY.			
8	9'	clayey, fine-gr. SAND.			
9	10'	Fine-gr. SANDSTONE.			
10'		LIMESTONE.			
			Elevation determined by arbitrary benchmark.		
			Casing height/grout variance granted by KDHE.		
		WELL ID: MW-4			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/5/91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 102 This Water Well Record was completed on (mo/day/yr) 4/5/91 under the business name of LATNE-WESTERN CO. by (signature) Paul L. Lane					