

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Johnson		SE 1/4 SW 1/4 SW 1/4	30	T 13 S	R 24 EW
Distance and direction from nearest town or city street address of well if located within city? Property immediately east of Texaco station, 1800 Santa Fe, Olathe					
2 WATER WELL OWNER: Texaco Refining and Marketing Inc.					
RR#, St. Address, Box # : 1437 S. Boulder				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code : Tulsa, OK 74119				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 8 ft. ELEVATION: 90.57			
		Depth(s) Groundwater Encountered 1. 5.67 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 5.73 ft. below land surface measured on mo/day/yr 5/11/91			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 7.25 in. to 8 ft., and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No ☒			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
2 PVC		4 ABS		6 Asbestos-Cement	
				9 Other (specify below)	
				8 Concrete tile	
				CASING JOINTS: Glued Clamped	
				Welded	
				Threaded ☒	
Blank casing diameter 4 in. to 2.5 ft., Dia		in. to ft., Dia		in. to ft.	
Casing height above land surface Ground Level in., weight		lbs./ft. Wall thickness or gauge No. Sch. 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel		5 Fiberglass	
2 Brass		4 Galvanized steel		6 Concrete tile	
				8 RMP (SR)	
				9 ABS	
				10 Asbestos-cement	
				11 Other (specify)	
				12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot		5 Gauzed wrapped	
2 Louvered shutter		4 Key punched		6 Wire wrapped	
				7 Torch cut	
				8 Saw cut	
				11 None (open hole)	
				9 Drilled holes	
				10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 2.5 ft. to 8 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 2 ft. to 8 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 1 ft. to 2 ft., From 0 ft. to 1 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines		7 Pit privy	
2 Sewer lines		5 Cess pool		8 Sewage lagoon	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard	
				10 Livestock pens	
				14 Abandoned water well	
				11 Fuel storage	
				15 Oil well/Gas well	
				12 Fertilizer storage	
				16 Other (specify below)	
				13 Insecticide storage	
Direction from well? West				How many feet? ~200	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1'	Pavement/subgrade			
1	7.5'	Varicolored, silty to fine sandy CLAY.			
7.5	8'	Fine-gr. SANDSTONE.			
8'		LIMESTONE.			
			Elevation determined by arbitrary benchmark.		
			Casing height/grout variance granted by KDHE.		
		WELL ID > MW-5			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/15/91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 102 This Water Well Record was completed on (mo/day/yr) 5/9/91 under the business name of LAYNE-WESTERN CO. by (signature) Paul W. Turner					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					