

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: JOHNSON		SW 1/4 SW 1/4 SE 1/4	30	T 13 S	R 24 E
Distance and direction from nearest town or city street address of well if located within city? AMOCO 1605 E. SANTA FE, OLATHE, KANSAS					
2 WATER WELL OWNER: AMOCO OIL COMPANY					
RR#, St. Address, Box # : 8700 INDIAN CREEK PKWAY				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code : OVERLAND PARK, KANSAS 66210				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 18.0 ft. ELEVATION: 100.71			
		Depth(s) Groundwater Encountered 1 8.15 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 8.15 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was NA ft. after hours pumping gpm			
		Est. Yield NA gpm Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 6 1/4 in. to 18.0 ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 0 in. to 3.5 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 3.5 ft. to 18.0 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft. From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 3.5 ft. to 1.5 ft., From 1.5 ft. to 0 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) FUEL TANKS 13 Insecticide storage					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3.5	SILTY CLAY, BROWN			
3.5	6.0	SILTY CLAY, GRAY			
6.0	8.5	SILTY CLAY, BROWN, VERY SUUFF			
8.5	13.5	MOTTLED CLAY, GRAY-BROWN			
13.5	16.5	CLAY, GRAY, SUUFF			
16.5	18.0	CLAY, SUUFF, GRAY			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-8-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. This Water Well Record was completed on (mo/day/yr) 6-25-91 under the business name of WEST HAZMAT DRILLING by (signature) <i>Harry H. Jankus</i>					