

1 LOCATION OF WATER WELL:		Fraction	Form WW-5		KSA 82a-1212	
County: Johnson		SE 1/4 SE 1/4 NE 1/4	Section Number 34		Township Number T 13 S	
Range Number R 24 E		Distance and direction from nearest town or city street address of well if located within city?				
2400' North at the intersection of 143rd + Quivira 70' west of Quivira Centerline		Overland Park KS				
2 WATER WELL OWNER: Water District #1		RR#, St. Address, Box # : 7315 Frontage Rd Ste 202				
City, State, ZIP Code : Overland Park KS 66204		Board of Agriculture, Division of Water Resources				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		Application Number:				
4 DEPTH OF COMPLETED WELL 15.5 ft. ELEVATION:		Depth(s) Groundwater Encountered 1. 7.0 ft. 2. ft. 3. ft.				
WELL'S STATIC WATER LEVEL 7.0 ft. below land surface measured on mo/day/yr		Pump test data: Well water was ft. after hours pumping gpm				
Est. Yield gpm: Well water was ft. after hours pumping gpm		Bore Hole Diameter 5 in. to 15.5 ft. and in. to ft.				
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well				
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Water level monitoring				
Was a chemical/bacteriological sample submitted to Department? Yes No X		If yes, mo/day/yr sample was submitted				
5 TYPE OF BLANK CASING USED:		Water Well Disinfected? Yes No				
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped		2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded				
Blank casing diameter 2 in. to 5.0 ft. Dia in. to ft. Dia in. to ft.		Casing height above land surface 36 in. weight 0.70 lbs./ft. Wall thickness or gauge No. Sch 40				
TYPE OF SCREEN OR PERFORATION MATERIAL:		PVC 10 Asbestos-cement				
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)				
1 Continuous slot 2 Mill slot 6 Wire wrapped 9 Drilled holes		2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)				
SCREEN-PERFORATED INTERVALS:		From 15.5 ft. to 5.0 ft. From ft. to ft.				
GRAVEL PACK INTERVALS:		From 15.5 ft. to 3.0 ft. From ft. to ft.				
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete				
Grout Intervals: From 3.0 ft. to 1.0 ft. From 1.0 ft. to 0.0 ft. From ft. to ft.		What is the nearest source of possible contamination:				
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well		2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well				
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)		13 Insecticide storage N/A				
Direction from well?		How many feet?				
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS						
0.0 1.0 Brown lean clay						
1.0 8.0 Gray Brown lean clay						
8.0 12.5 Gray Brown Fat Clay						
12.5 13.5 Limestone						
13.5 15.5 Gray shale						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/22/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 516 This Water Well Record was completed on (mo/day/yr) 10/26/93 under the business name of Geosystems Engineering Inc by (signature)						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						