

CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

County: Johnson

Location listed as:

Section-Township-Range: 12-135-24EFraction ($\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$): NW NW

Location changed to:

12-135-24ENE NW NWOther changes: Initial statements: Wyandotte CountyChanged to: Johnson County

Comments: _____

verification method: Legal description, well owner's address,
city street map, and Lenexa 1:24,000 topo. map.initials: DR date: 10/7/2005

1 LOCATION OF WATER WELL: County: <u>Wyandotte</u>		Fraction $\frac{1}{4}$ <u>NW</u> $\frac{1}{4}$ <u>NW</u> $\frac{1}{4}$	Section Number <u>12</u>	Township Number T <u>13 S</u> S	Range Number R <u>24 E</u> E/W	
Distance and direction from nearest town or city street address of well if located within city?						
2 WATER WELL OWNER: <u>Texaco</u> RR#, St. Address, Box #: <u>10075 W. 103rd St.</u> City, State, ZIP Code: <u>Overland Park, Kansas</u> Board of Agriculture, Division of Water Resources Application Number:						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 1 Mile		4 DEPTH OF COMPLETED WELL: <u>12</u> ft. ELEVATION: ft. Depth(s) Groundwater Encountered 1. <u>8</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>8</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>8 1/4</u> in. to <u>12</u> ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10 Monitoring well</u> Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No				
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped <u>2 PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>2</u> in. to <u>5</u> ft. Dia in. to ft. Dia in. to ft. Casing height above land surface: <u>Flush</u> in., weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: <u>1 Continuous slot</u> 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 3 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From <u>5</u> ft. to <u>12</u> ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From <u>3</u> ft. to <u>12</u> ft. From ft. to ft. From ft. to ft. From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>3 Bentonite</u> 4 Other Grout Intervals: From <u>0</u> ft. to <u>18"</u> ft. From <u>18"</u> ft. to <u>3</u> ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? How many feet?						
FROM		TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>5</u>		<u>Silty Clay (Brown)</u>			
<u>5</u>	<u>8</u>		<u>Tan Limestone</u>			
<u>8</u>	<u>12</u>		<u>Grey Shale</u>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>9-8-97</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>607</u> This Water Well Record was completed on (mo/day/yr) under the business name of <u>Davis Environmental Drilling L.L.C.</u> by (signature) <u>[Signature]</u>						