

WATER WELL RECORD

Form WWC-5

Division of Water Resources App. No.

1 LOCATION OF WATER WELL: County: <u>Johnson</u>		Fraction <u>SE 1/4 SW 1/4 SW 1/4 SW 1/4</u>	Section Number <u>33</u>	Township No. <u>T 13 S</u>	Range Number <u>R 25 NE</u> ☒ <u>W</u>																																																																								
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here ☐ <u>5108 W. 142nd Terrace Overland Park KS</u>			Global Positioning System (GPS) information: Latitude: (in decimal degrees) Longitude: (in decimal degrees) Elevation: Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27 Collection Method: ☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m																																																																										
2 WATER WELL OWNER: <u>Kevin Lutz</u> RR#, Street Address, Box #: <u>P.O. Box 23424</u> City, State, ZIP Code: <u>Shawnee KS 66284</u>																																																																													
3 LOCATE WELL WITH AN "X" IN SECTION BOX: N W E S [Diagram: A 3x3 grid with 'NW', 'NE', 'SW', 'SE' in the corners. An 'X' is marked in the bottom-left cell (SW).] [Diagram: A horizontal line with 'S' in the center and '1 mile' below it.]		4 DEPTH OF COMPLETED WELL <u>Plugged</u> <u>360</u> ft. <u>5-360' bores</u> Depth(s) Groundwater Encountered (1) <u>None</u> ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL <u>None</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm EST. YIELD gpm. Well water was ft. after hours pumping gpm Bore Hole Diameter in. to ft., and in. to ft. WELL WATER TO BE USED AS: ☐ Public water supply ☒ Geothermal ☐ Injection well ☐ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below) ☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well <u>Closed loop</u> Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☒ No If yes, mo/day/yr sample was submitted Water well disinfected? ☐ Yes ☒ No																																																																											
5 TYPE OF CASING USED: ☐ Steel ☐ PVC ☒ Other <u>H.D. Polyethylene</u> CASING JOINTS: ☐ Glued ☐ Clamped ☒ Welded ☐ Threaded <u>Fusion</u> Casing diameter in. to <u>360</u> ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface <u>below</u> <u>36</u> in., Weight <u>SQR11</u> lbs./ft., Wall thickness or gauge No. <u>160 P.S.I.</u> TYPE OF SCREEN OR PERFORATION MATERIAL: ☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify) ☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: <u>None</u> ☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft. From ft. to ft., From ft. to ft.																																																																													
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☒ Bentonite ☐ Other Grout Intervals: From <u>360</u> ft. to <u>3</u> ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: ☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well Direction from well Distance from well																																																																													
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>LITHO. LOG (cont.) or PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>13</td> <td>Spil + clay</td> <td></td> <td></td> <td></td> </tr> <tr> <td>13</td> <td>32</td> <td>lime</td> <td></td> <td></td> <td></td> </tr> <tr> <td>32</td> <td>39</td> <td>Shale</td> <td></td> <td></td> <td></td> </tr> <tr> <td>39</td> <td>42</td> <td>lime</td> <td></td> <td></td> <td></td> </tr> <tr> <td>42</td> <td>44</td> <td>Shale</td> <td></td> <td></td> <td></td> </tr> <tr> <td>44</td> <td>46</td> <td>lime</td> <td></td> <td></td> <td></td> </tr> <tr> <td>46</td> <td>57</td> <td>Shale</td> <td></td> <td></td> <td></td> </tr> <tr> <td>57</td> <td>65</td> <td>lime</td> <td></td> <td></td> <td></td> </tr> <tr> <td>65</td> <td>69</td> <td>Shale</td> <td></td> <td></td> <td></td> </tr> <tr> <td>69</td> <td>74</td> <td>lime</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td>360</td> <td>3</td> <td>5-360' Bores plugged with High Solid Bentonite</td> </tr> </tbody> </table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHO. LOG (cont.) or PLUGGING INTERVALS	0	13	Spil + clay				13	32	lime				32	39	Shale				39	42	lime				42	44	Shale				44	46	lime				46	57	Shale				57	65	lime				65	69	Shale				69	74	lime							360	3	5-360' Bores plugged with High Solid Bentonite
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHO. LOG (cont.) or PLUGGING INTERVALS																																																																								
0	13	Spil + clay																																																																											
13	32	lime																																																																											
32	39	Shale																																																																											
39	42	lime																																																																											
42	44	Shale																																																																											
44	46	lime																																																																											
46	57	Shale																																																																											
57	65	lime																																																																											
65	69	Shale																																																																											
69	74	lime																																																																											
			360	3	5-360' Bores plugged with High Solid Bentonite																																																																								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo/day/year) <u>12-29-10</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>561</u> This Water Well Record was completed on (mo/day/year) <u>12-29-10</u> under the business name of <u>E.V.A.S. Energy Dev. Inc.</u> by (signature) <u>[Signature]</u>																																																																													
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html .																																																																													