

1] LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Dickinson	SE 1/4 SE 1/4 SE 1/4	6	T 13 S	R 3 E/A*

Distance and direction from nearest town or city street address of well if located within city?
 3 1/2 miles East of Abilene, Ks from Hwy 15 on old Hwy 40 & 1 North & 3/4 mile East

2] WATER WELL OWNER: Mickey Cook
 RR#, St. Address, Box # : 2383 Lark Rd
 City, State, ZIP Code : Abilene, Kansas 67410
 Board of Agriculture, Division of Water Resources
 Application Number:

3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4] DEPTH OF COMPLETED WELL: 77 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. 5.3 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL: 5.0' 6" ft. below land surface measured on mo/day/yr 8. / . 20. / . 0.2

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 1.5+ gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter: 9 in. to 7.7 ft., and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes. No. * ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes * No

5] TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued. . . * . Clamped.
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
		7 Fiberglass		Threaded.

Blank casing diameter 5 in. to 7.7 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface. 1.4 in., weight 200 lbs./ft. Wall thickness or gauge No. 250

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	ft.

SCREEN-PERFORATED INTERVALS: From 5.1 ft. to 7.7 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 2.3 ft. to 7.7 ft., From ft. to ft.

6] GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 23 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? NORTH APPROX How many feet? 220

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	DARK SANDY TOP SOIL			
1	14	LITE COLOR & LITE GRAY SHALE			
14	17	LITE COLOR LIMESTONE			
17	25	LITE COLOR SHALE			
25	27	RED SHALE			
27	35	LITE COLOR SHALE & CLAY			
35	39	RED & GRAY SHALE MIXED			
39	53	LITE COLOR SHALE			
53	57	LITE COLOR LIMESTONE			
57	77	GRAY SHALE & CLAY			

7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8. / . 20. / . 02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 397 This Water Well Record was completed on (mo/day/yr) 9. / . 2. / . 02 under the business name of CENTRAL KANSAS DRILLING by (signature) *Harold D. Martin*