

1] LOCATION OF WATER WELL: Fraction SE ¼ SE ¼ SE ¼ Section Number 6 Township Number T 13 S Range Number R 3 **SW***
 County: Dickinson
 Distance and direction from nearest town or city street address of well if located within city?
4 ½ miles East of Abilene, Ks from Hwy 15 on old Hwy 40 & 1 mile North

2] WATER WELL OWNER: Mike & Judy Powell
 RR#, St. Address, Box # : 2403 Lark Rd Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Abilene, Kansas 67410 Application Number:

3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4] DEPTH OF COMPLETED WELL: 141 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 103 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 102 ft. below land surface measured on mo/day/yr 8 / .27 / .02
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 1.5 gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter. 9 in. to 14.1 ft., and in. to ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes. No. *; If yes, mo/day/yr sample was sub-
 mitted Water Well Disinfected? Yes * No

5] TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued. * Clamped.
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 2 PVC 4 ABS 7 Fiberglass Threaded.
 Blank casing diameter 5 in. to 14.1 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface. 12 in., weight 200 lbs./ft. Wall thickness or gauge No. 250
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 10.1 ft. to 14.1 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 24 ft. to 14.1 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6] GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 2 ft. to 24 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? SOUTHWEST How many feet? 133

FROM	TO	LITHOLOGIC LOG	FROM	TO	PERFORATION INTERVALS*
0	2 ½	FINE SAND	76	80	LITE COLOR SHALE
2 ½	7	BROWN & TAN & GRAY MIXED CLAY	80	82	LITE GRAY SHALE
7	17	BROWN FINE SAND	82	94	RED SHALE
17	18	LITE COLOR LIMESTONE	94	99	TAN CLAY & SHALE
18	26	LITE COLOR SHALE & CLAY	99	117	HARD LITE COLOR LIMESTONE
26	28	MAHROON SHALE & CLAY	117	122	GRAY CLAY & SHALE
28	36	LITE COLOR SHALE	122	129	LITE COLOR CLAY SHALE & G
36	44	GRAY & MAHROON SHALE MIXED			GRAY STREEKS
44	45	LITE COLOR SHALE	109	133	LITE COLOR LIMESTONE
45	47	LITE COLOR LIMESTONE	133	136	LITE COLOR CLAY & SHALE
47	57	LITE COLOR SHALE	136	141	LITE GRAY SHALE
57	62	LITE COLOR LIMESTONE			
62	64	LITE COLOR SHALE			
64	76	GRAY SHALE			

7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8 / .27 / .02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 397 This Water Well Record was completed on (mo/day/yr) 9 / .2 / .02 under the business name of CENTRAL KANSAS DRILLING by (signature) Harold D. Martin