

1 LOCATION OF WATER WELL: County: Dickinson	Fraction NW ¼ NE ¼ NE ¼	Section Number 5	Township Number T 13 S	Range Number R 4 E 1/4
--	----------------------------	---------------------	---------------------------	---------------------------

Distance and direction from nearest town or city street address of well if located within city?  
1 mile South of Chapman, Ks & 3/4 miles East

2 WATER WELL OWNER: Jim Canfield  
 RR#, St. Address, Box #: 2084 - 2599 Ave.  
 City, State, ZIP Code: Chapman, Kansas 67431  
 Board of Agriculture, Division of Water Resources  
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N	1 *
2	3
4	6
S	

4 DEPTH OF COMPLETED WELL: 45' 6" ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 10' 8" ft. 2. 12' ft. 3. ft.  
 WELL'S STATIC WATER LEVEL 10' 8" ft. below land surface measured on mo/day/yr 11 / 25 / 96  
 Pump test data: Well water was ft. after hours pumping gpm  
 Est. Yield 15+ gpm: Well water was ft. after hours pumping gpm  
 Bore Hole Diameter 9 in. to 4.5 1/2 ft., and in. to ft.  
 WELL WATER TO BE USED AS:  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes No \*; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes \* No

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued \* Clamped  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
 7 Fiberglass Threaded  
 Blank casing diameter 5 in. to 4.5' 6" ft., Dia in. to ft., Dia in. to ft.  
 Casing height above land surface 1.6 in., weight 160 lbs./ft. Wall thickness or gauge No. 214  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 11 Other (specify)  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 12 ft. to 45 ft., From ft. to ft.  
 From ft. to ft., From ft. to ft.  
 GRAVEL PACK INTERVALS: From 10 ft. to 4.5 1/2 ft., From ft. to ft.  
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? WEST APPROX How many feet? 250

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	DARK TOP SOIL			
1	10 6	BROWN CLAY			
10 6	24	LITE COLOR LIMESTONE			
24	28	DARK LIMESTONE			
28	39	LITE TAN LIMESTONE			
39	43	GRAY SHALE			
43	45 1/2	DARK BLUE FLINT			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11 / 25 / 96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 397 This Water Well Record was completed on (mo/day/yr) 11 / 29 / 96 under the business name of CENTRAL KANSAS DRILLING by (signature) Harold D. Martin