	WAT	ER WELL RECORD Fo	orm WWC-5 KSA	82a-1212	
LOCATION OF WATER WI		or er	Section Numb	'.	
Dounty: Learny	SW 1/4	SE 1/4 SE	1/4 30		S R & E/W
Distance and direction from n	learest town or city?	d 3 miles hon	Street address of we	Il if located within city?	hoide of road
RR#, St. Address, Box # :	. O				Iture, Division of Water Resources
City, State, ZIP Code :	AltaV	ista Ka	ns 668.	3 Application Nun	nber:
DEPTH OF COMPLETED	· WELL	Bore Hole Diameter	<i>[. 0</i> in. to <i>[</i>	.5 ft., and 6-	5 in. to ft.
Nell Water to be used as:	5 Public water		8 Air conditioning	11 Injection	
Domestic 3 Feedlot	6 Oil field water		9 Dewatering	12 Other ((Specify below)
2 Irrigation 4 Industria			10 Observation well	g watering	1001
	⊃ ft. below lar	nd surface measured on	· · · · · · / · · · · · · · · ·	.month	day
Pump Test Data Est. Yield /	gpm: Well water was	π. aπer ft. after		hours pumping	gpm
1 TYPE OF BLANK CASING	G USED:	5 Wrought iron	8 Concrete tile	Casing Joints	: Glued . 🗶 Clamped
1 Steel 3	RMP (SR)	6 Asbestos-Cement	9 Other (specify b	elow)	Welded
	4 ABS	7 Fiberglass			Threaded
					in. to ft.
Casing height above land sur	face 	in., weight;		lbs./ft. Wall thickness or g	auge No 2.67 Walf
TYPE OF SCREEN OR PER			(7 PVC)	10 Asbestos	
	3 Stainless steel	5 Fiberglass	8 RMP (SR)	, ,	pecify)
	4 Galvanized steel	6 Concrete tile	9 ABS	P. C.	ed (open hole)
Screen or Perforation Openin		5 Gauzed	• •	. 8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wr	• •	9 Drilled holes	
	Key punched in to	7 Torch c		`	in toft.
Screen-Perforated Intervals:					ft. toft.
borden enorated intervals.	From	ft. to	ft. From		ft. to
Gravel Pack Intervals:					ft. to
	From	ft. to	ft., From		ft. to ft.
5 GROUT MATERIAL:	1 Neat cement	2 Cement grout			
Grouted Intervals: From	ft. to	ft., From	ft. to	_. ft., From	ft. to
What is the nearest source of	f possible contamination:	trade	10 F	uel storage	14 Abandoned water well
1 Septic tank	4 Cess pool	7 Sewage lagoo	n 11 F	ertilizer storage	15 Oil well/Gas well
2 Sewer lines	5 Seepage pit	8 Feed yard		secticide storage	16 Other (specify below)
3 Lateral lines Direction from well.	Pit privy	9 Livestock pens	13 W	Vatertight sewer lines	
Direction from well V.V.	MI W. ROY	w many feet		ater Well Disinfected? Yes	X No
was a chemical/bacteriologic was submitted	·	1		- "	
Depth of Pump Intake	maine		Pumps Capacity rated	d at	
•				Dentrifugal 5 Recip	•
					ged under my jurisdiction and was
completed on	and the same of th		Andreas and the second	1 02	8/ year
and this record is true to the					
This Water Well Record was		mo	nth	day 0 19	$\mathcal{E}f$ year under the business
name of strade	, Drilling	COC by	y (signature) Har	old Strades	
7 LOCATE WELL'S LOCAT	ION FROM JO	LITHOLOGIC	CLOG F	ROM TO	LITHOLOGIC LOG
WITH AN "X" IN SECTION BOX:	0 0	Top Soil	Black) // // // // // // // // // // // // //	
	5 15	Ir oep,	une yell	eu	
N	1.5 30	shale,"	sene,		
NW NE	30 36	1 21 1	Sute lunes	. Y	
	36 76	Trock, "	al. o	rost	
i w	1669	shall,	serce		
SW SE	6974	Shale 1	orl		
N. J.	0111	37	and the second s		
5 1 Mile					
ELEVATION:		2 TERRITORIUS (4 A. 14 A		4.0000000000000000000000000000000000000	
Depth(s) Groundwater Encou	untered 1	. 2 ft. 3	ft. 4	ft. (Use a sec	cond sheet if needed)
INSTRUCTIONS: Use typewi	riter or ball point ' peñ, <i>pl</i> ea	se press firmly and PRINT	clearly. Please fill in b	lanks, underline or circle th	e correct answers. Send top three
- cooles to Kansas Denartment	ALEMPHIC SHOPEN FOURTONNESS	L LIVISION Of Environment V	vater vvell Contractors	, торека, KS 66620. Send (one to WATER WELL OWNER and