


1 LOCATION OF WATER WELL: County: NABUNSEE		Fraction SE 1/4 SE 1/4 SW 1/4	Section Number 4	Township Number T 14 S	Range Number R 11 E
Distance and direction from nearest town or city street address of well if located within city? 4.5 W + 1 S of Eskridge					
2 WATER WELL OWNER: CORBETT WORKMAN RR#, St. Address, Box #: CABIN No 230 Box 92 City, State, ZIP Code: RA ALMA KS 66401			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 42 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 21 ft. below land surface measured on mo/day/yr JAN 4-83 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 2 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 10 in. to 15 ft., and 6 1/4 in. to 50 ft. WELL WATER TO BE USED AS: <input checked="" type="checkbox"/> Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes <input checked="" type="checkbox"/> No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? <input checked="" type="checkbox"/> Yes No			
5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) Blank casing diameter 5 in. to 38 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface 12 in., weight 30A 26 lbs./ft. Wall thickness or gauge No. 0.203 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 11 None (open hole) SCREEN-PERFORATED INTERVALS: From 38 ft. to 50 ft., From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From NO ft. to ft., From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: <input checked="" type="checkbox"/> Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 16 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: <input checked="" type="checkbox"/> Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? SW How many feet? 130					
FROM TO LITHOLOGIC LOG			FROM TO LITHOLOGIC LOG		
0	1	SOIL			
1	3	ROCKY SOIL			
3	12	LIME			
12	18	SHALE			
18	19	LIME			
19	26	SHALE			
26	28	LIME			
28	34	SHALE			
34	50	LIME WITH BREAKS			
WATER AT 42' 2 GPM					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) JAN 4-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 119 This Water Well Record was completed on (mo/day/yr) JAN 4-83 under the business name of JURMAN DAOS DRILLING CO by (signature) <i>[Signature]</i> INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					