

Don't CK - have done enough in this area

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: WABAUNSEE Fraction: NW 1/4 NW 1/4 NE 1/4 Section Number: 9 Township Number: T 14 S Range Number: R 11 E

2 Distance and direction from nearest town or city street address of well if located within city? 4 1/2 W. of Eskridge LOT # 261 LAKE WABAUNSEE

3 WATER WELL OWNER: Hendricks Hdwe. + Supply

4 RR#, St. Address, Box #: Alma, Kansas 66401 Board of Agriculture, Division of Water Resources Application Number:

5 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

6 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION: 30 ft.

7 Depth(s) Groundwater Encountered: 28 ft. below land surface measured on mo/day/yr 6-24-81

8 WELL'S STATIC WATER LEVEL: 28 ft. below land surface measured on mo/day/yr 6-24-81

9 Pump test data: Well water was 1/2 gpm: Well water was 8 ft. after 80 hours pumping 80 gpm

10 Est. Yield: 1/2 gpm: Well water was 8 ft. after 80 hours pumping 80 gpm

11 Bore Hole Diameter: 8 in. to 80 ft. and 80 in. to 80 ft.

12 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

13 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted

14 Water Well Disinfected? Yes No

15 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
2 PVC 4 ABS 7 Fiberglass Threaded

16 Blank casing diameter: 5 in. to 0-20 ft. Dia. 5 in. to 50-80 ft. Dia. 258 lbs./ft. Wall thickness or gauge No. 258

17 Casing height above land surface: 24 in. weight 284 lbs./ft.

18 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

19 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

20 SCREEN-PERFORATED INTERVALS: From 20 ft. to 50 ft. From 20 ft. to 50 ft.

21 GRAVEL PACK INTERVALS: From 10 ft. to 80 ft. From 10 ft. to 80 ft.

22 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

23 Grout Intervals: From 0 ft. to 10 ft. From 0 ft. to 10 ft.

24 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

25 Direction from well? NE How many feet? 100

26 LITHOLOGIC LOG

FROM	TO	LITHOLOGIC LOG
0	1	TS
1	6	LS - Lime Stone
6	20	Shale & Limestone
20	40	Shale Rock & Limestone
40	80	Shale Grey

27 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) June 24, 1981 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 6-30-81 under the business name of Stader Drilling Co., Inc. by (signature) Dale Fisher

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.