County: WABAUNSEE NW 1/4 NW 1/4 NW 1/4 P T 1/4 S R 1/2 Distance and direction from nearest town or city street address of well if located within city? 1/4 mile south, 1/4 east of Eskridge WATER WELL OWNER: Monty or Dorothy Hase RR#, St. Address, Box #: Rt. 1 City, State, ZIP Code : Eskridge, KS 66423 Application Number: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: WELL'S STATIC WATER LEVEL . 64	ft. 38gpmgpmgpm
Distance and direction from nearest town or city street address of well if located within city? 1/4 mile south, 1/4 east of Eskridge WATER WELL OWNER: Monty or Dorothy Hase RR#, St. Address, Box #: Rt. 1 City, State, ZIP Code	ater Resourceft. 38gpmgpm
WATER WELL OWNER: Monty or Dorothy Hase RR#, St. Address, Box #: Rt. 1 City, State, ZIP Code : Eskridge, KS 66423 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: WELL'S STATIC WATER LEVEL . 64." ft. below land surface measured on mo/day/yr . 12-21-i pump test data: Well water was ft. after hours pumping . Est. Yield . 8. gpm: Well water was ft. after hours pumping . Bore Hole Diameter . 8. 3/4. in. to	ft. 38gpmgpmgpm
WATER WELL OWNER: Monty or Dorothy Hase RR#, St. Address, Box # : Rt. 1 City, State, ZIP Code : Eskridge, KS 66423 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: WELL'S STATIC WATER LEVEL .64. ft. below land surface measured on mo/day/yr .12-21-i Pump test data: Well water was ft. after hours pumping . Est. Yield & gpm: Well water was ft. after hours pumping . Bore Hole Diameter .8 .3/4. in. to ft., and in. to well water supply 8 Air conditioning 11 Injection well 1 Domestic 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well water Well Disinfected? Yes X No. TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued .X . Clar Clars Stank casing diameter 5. in. to .0-85 ft., Dia 5. in. to .100-140 ft., Dia in. to	ft. 38gpmgpmgpm
Board of Agriculture, Division of Water Well Disinfected? Yes X No TYPE OF BLANK CASING USED: State 3 RMP (SR) State 4 RM (SR) State 4 RME (SR) State 4 RM (SR) Sta	ft. 38gpmgpmgpm
City, State, ZIP Code : Eskridge , KS 66423 Application Number: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered 1 96' ft. 2 ft. 3	ft. 38gpmgpmgpm
LOCATE WELL'S LOCATION WITH A DEPTH OF COMPLETED WELL. 140! ft. ELEVATION: Depth(s) Groundwater Encountered 1. 96! ft. 2. ft. 3. WELL'S STATIC WATER LEVEL. 64! ft. below land surface measured on mo/day/yr. 12-21-in. Pump test data: Well water was ft. after hours pumping. Est. Yield. 8. gpm: Well water was ft. after hours pumping. Bore Hole Diameter. 8. 3/4. in. to ft., and ft., and in. to ft., and in., and in. to ft., and in., and in., a	ft. 38gpmgpmgpm
Depth(s) Groundwater Encountered 1. 96 ft. 2. ft. 3. WELL'S STATIC WATER LEVEL . 64 ft. below land surface measured on mo/day/yr . 12-21-6 Pump test data: Well water was ft. after hours pumping Bore Hole Diameter . 8 . 3 / 4. in. to ft., and in. to WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Water Well Disinfected? Yes X No TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued . X . Clar 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Pump test data: Well water was ft. after hours pumping Bore Hole Diameter . 8 . 3 / 4. in. to ft., and in. to in. to	ft. 38gpmgpmgpm
WELL'S STATIC WATER LEVEL .64 ft. below land surface measured on mo/day/yr .12-21-decomposition of the property of th	38 gpm gpm
Pump test data: Well water was ft. after hours pumping	gpm gpn ft y below)
Est. Yield . 8. gpm: Well water was ft. after hours pumping	gpnft
Bore Hole Diameter 8. 3/4. in. to	
TYPE OF BLANK CASING USED: 1 Steel 2 RMP (SR) 4 ABS 7 Fiberglass 5 In. to .0-85 6 Oil field water supply 9 Dewatering 12 Other (Specifical Matter) 10 Monitoring well Water Well Disinfected? Yes X No 8 Concrete tile CASING JOINTS: Glued X Clar 9 Other (specify below) Welded Threaded Threaded Casing height above land surface 2 Indicate: 1 Domestic 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Water Well Disinfected? Yes X No 8 Concrete tile CASING JOINTS: Glued X Clar 9 Other (specify below) Welded Threaded Casing height above land surface 24" in., weight 2 82 Ibs./ft. Wall thickness or gauge No	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes	
\$ mitted Water Well Disinfected? Yes X No TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clar 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded. Blank casing diameter 5" in. to 0-85 ft., Dia 5" in. to .100-140 ft., Dia in. to Casing height above land surface 24" in., weight 2.82 lbs./ft. Wall thickness or gauge No25	mple was su
TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X . Clar 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded	
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter 5" in. to .0-85 ft., Dia .5" in. to .100-140 ft., Dia in. to Casing height above land surface 24" in., weight 2.82 lbs./ft. Wall thickness or gauge No	
2 PVC 4 ABS 7 Fiberglass Threaded. Blank casing diameter 5"in. to .0-85	
Blank casing diameter 5 " in to $0-85$ ft., Dia 5 " in to $100-140$ ft., Dia in to .25. Casing height above land surface 24 " in., weight 2.82 lbs./ft. Wall thickness or gauge No25.	
Casing height above land surface	
	,
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (o)	en hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	,
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 85 ft. to	
From ft. to ft., From ft. to ft.	
GRAVEL PACK INTERVALS: From 24	
From ft. to ft., From ft. to	ft
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other	
Grout Intervals: From4ft. toft., Fromft. toft., Fromft. to	
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned wa	
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas we 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify)	
to the control of the	•
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? How many feet? 220	• • • • • • • • •
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	
0 1 Top Soil	
1 5 Clay-Brown	
5 20 Limestone-Yellow	
20 51 Shale-Yellow	
51 53 Limestone-Yellow	
53 55 Shale-Red	
55 58 Shale-Yellow	
58 61 Limestone-Yellow	
61 65 Shale-yellow	
61 65 Shale-yellow Shale-Black	
61 65 Shale-yellow 65 75 Shale-Black 75 88 Shale-Yellow	
61 65 Shale-yellow 65 75 Shale-Black 75 88 Shale-Yellow 88 96 Limestone-Yellow-Loose	
61 65 Shale-yellow 65 75 Shale-Black 75 88 Shale-Yellow	
61 65 Shale-yellow 65 75 Shale-Black 75 88 Shale-Yellow 88 96 Limestone-Yellow-Loose	
61 65 Shale-yellow 65 75 Shale-Black 75 88 Shale-Yellow 88 96 Limestone-Yellow-Loose 96 140 Shale-Grey	
61 65 Shale-yellow 65 75 Shale-Black 75 88 Shale-Yellow 88 96 Limestone-Yellow-Loose 96 140 Shale-Grey CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdice.	
61 65 Shale-yellow 65 75 Shale-Black 75 88 Shale-Yellow 88 96 Limestone-Yellow-Loose 96 140 Shale-Grey CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdict completed on (mo/day/year)	
61 65 Shale-yellow 65 75 Shale-Black 75 88 Shale-Yellow 88 96 Limestone-Yellow-Loose 96 140 Shale-Grey CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdict completed on (mo/day/year)	
61 65 Shale-yellow 65 75 Shale-Black 75 88 Shale-Yellow 88 96 Limestone-Yellow-Loose 96 140 Shale-Grey CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdict completed on (mo/day/year)	pelief. Kansa