WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.	
1 LOCATION OF WATER WELL:	Fraction	Section Number Township No. Range Number	
County: OSage	NW4 NE14 NE1/4 NW1/4		
Street/Rural Address of Well Location; i		Global Positioning System (GPS) information:	
from nearest town or intersection: If at o	owner's address, check here	Latitude: (in decimal degrees) Longitude: (in decimal degrees)	
		Elevation: (in decimal degrees)	
		<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27	
2 WATER WELL OWNER: Bryan RR#, Street Address, Box #: 2919	2 Carolyn Kemble	Collection Method:	
City, State, ZIP Code : 2919	5w 133 cp 5r	☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey	
	odale, KS 66414	Est. Accuracy: \square <3 m, \square 3-5 m, \square 5-15 m, \square >15 m	
3 LOCATE WELL	Magica		
WITH AN "X" IN 4 DEPTH OF 6	SOMPLETED WELL	duQft. 4-200 Bores	
SECTION BOX: Depth(s) Ground	TE WELL AN "X" IN ON BOX: Depth(s) Groundwater Encountered (1)55-142ft. (2)		
The same are the same as a same as	onm Well water was	ft. after hours pumping gpm	
W - NW - NE - EST. YIELD.	eter La in to 200	ft., andin. toft.	
WELL WATER	TO BE USED AS: Public wa	ater supply	
SW SE - Domestic Feedlot Oil field water supply Dewatering Other (Specify below)			
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well Closed			
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted			
	fected? Tyes 🛣 No		
5 TYPE OF CASING USED: Steel PVC Other H.DPolyachander Co. C. Casing joints: Glued Glamped W. Welded G. Threaded Fig. 190			
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter In to In to			
Casing height above land surface. 36 in., Weight S.O.R.II			
L TYPE OF SCREEN OR PERFORATION MATERIAL: . New grant 1			
Steel Stainless Steel PVC Other (Specify)			
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: № №			
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)			
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)			
SCREEN-PERFORATED INTERVALS: From			
From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From. ft. to ft., From ft. to ft. From. ft. to ft., From ft. to ft.			
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other			
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other			
What is the nearest source of possible contamination:			
	nes Pit privy Livestock		
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well			
Direction from well		ce from well	
FROM TO LITHOLOG		TO LITHO. LOG (cont.) or PLUGGING INTERVALS	
0 8 Soil+clay 8 41 Shale			
8 41 Shale			
41 52 Sandstone 52 35 Shale			
52 55 Shale	200	3 4-200 bores plugged with	
55 142 Sandstone		High Solid BEXtenite	
142 200 Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 🗓 constructed, 🗌 reconstructed, or 🗓 plugged under my jurisdiction and was completed on (mo/day/year)			
under my jurisdiction and was completed on (mo/day/year)			
Kansas Water Well Contractor's License No. 56.1 This Water Well Record was completed on (mo/day/year)			
under the business name of EUSAS. EARTGY. Dec. LAC. by (signature)			
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.			
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.			
KSA 82a-1212			