

1 LOCATION OF WATER WELL
 County: Dickinson Fraction SW 1/4 SE 1/4 SW 1/4 Section Number 21 Township Number T 14 S Range Number R 20 SW

Distance and direction from nearest town or city? Abilene 4 E Street address of well if located within city?

2 WATER WELL OWNER: Dan Reiff
 RR#, St. Address, Box #: DR Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Abilene KS 67410 Application Number:


3 DEPTH OF COMPLETED WELL: 70 ft. Bore Hole Diameter: 4 in. to 15 ft., and 7 in. to 70 ft.
 Well Water to be used as:
 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well
 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 7 Lawn and garden only 10 Observation well
 Well's static water level: 40 ft. below land surface measured on 6 month 16 day 00 year
 Pump Test Data: 15 gpm: Well water was 15 ft. after 15 hours pumping. 15 gpm
 Est. Yield: Well water was 15 ft. after 15 hours pumping. 15 gpm

4 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile Casing Joints: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing dia: 5 in. to 50 ft., Dia 15 in. to 160 lbs./ft. Wall thickness or gauge No Class 160
 Casing height above land surface: 15 in., weight Class 160
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 Screen or Perforation Openings Are:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 Screen-Perforation Dia: 5 in. to 70 ft., Dia 70 in. to 70 ft., Dia
 Screen-Perforated Intervals: From 5-0 ft. to 70 ft., From 70 ft. to 70 ft., From 70 ft. to 70 ft.
 Gravel Pack Intervals: From 13 ft. to 70 ft., From 70 ft. to 70 ft., From 70 ft. to 70 ft.

5 GROUT MATERIAL:
 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grouted Intervals: From 5 ft. to 13 ft., From 13 ft. to 70 ft., From 70 ft. to 70 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Cess pool 7 Sewage lagoon 11 Fertilizer storage 14 Abandoned water well
 2 Sewer lines 5 Seepage pit 8 Feed yard 12 Insecticide storage 15 Oil well/Gas well
 3 Lateral lines 6 Pit privy 9 Livestock pens 13 Watertight sewer lines 16 Other (specify below)
 Direction from well: E How many feet: 150? Water Well Disinfected? Yes No
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, date sample was submitted: 15 month 16 day 00 year Pump Installed? Yes No Volts
 If Yes: Pump Manufacturer's name: Boachus Drilling Model No. 180 HP 180 Volts
 Depth of Pump Intake: 15 ft. Pumps Capacity rated at: 15 gal./min.
 Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other

6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on 6 month 16 day 00 year and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 180
 This Water Well Record was completed on 15 month 16 day 00 year under the business name of Boachus Drilling by (signature) Paul Boachus

7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top Soil			
2	24	Clay - Shale			
24	30	Lime			
30	60	Blue Shale			
60	61	Water			
61	70	Shale			

ELEVATION:

Depth(s) Groundwater Encountered 1. 15 ft. 2. 15 ft. 3. 15 ft. 4. 15 ft. (Use a second sheet if needed)

INSTRUCTIONS: Use typewriter or ball point pen, please press firmly and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
R
2
EW
SEC.
SW 1/4
SE 1/4
SW 1/4