

1] LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Dickinson</u>	<u>NW 1/4 NE 1/4 NW 1/4</u>	<u>27</u>	<u>T 14 S</u>	<u>R 2 E/W</u>

Distance and direction from nearest town or city street address of well if located within city?
5 miles West of Hwy 43 of Navarre, Ks go 1 mile North & 3/8 mile East

2] WATER WELL OWNER: Kevin Whitehair
 RR#, St. Address, Box # : 915 N.W. 3rd St Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Abilene, Kansas 67410 Application Number:

3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4] DEPTH OF COMPLETED WELL. <u>80</u> ft. ELEVATION:
---	--

Depth(s) Groundwater Encountered 1. 67 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 60 ft. below land surface measured on mo/day/yr 9 / 7 / 02

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 12 gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter. 9 in. to 80 ft., and. in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Domestic (lawn & garden)
		9 Dewatering
		12 Other (Specify below)
		10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes. No. * ; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes * No

5] TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	CASING JOINTS: Glued. * Clamped.
2 PVC	4 ABS	7 Fiberglass		Welded
				Threaded.

Blank casing diameter 5 in. to 80 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface. 24 in., weight 200 lbs./ft. Wall thickness or gauge No. 250

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify) ft.

SCREEN-PERFORATED INTERVALS: From. 60 ft. to 80 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From. 24 ft. to 80 ft., From ft. to ft.

6] GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From. 3 ft. to 24 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? SOUTH WILL BE APPROX How many feet? 200

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	7	LITE COLOR SHALE			
7	26	LITE COLOR CLAY			
26	27	LITE COLOR LIMESTONE			
27	44	LITE COLOR SHALE			
44	46	LITE COLOR LIMESTONE			
46	53	LITE COLOR CLAY & SHALE			
53	56	LITE GRAY CLAY & RED MIXED			
56	59	LITE COLOR & LITE GRAY SHALE			
59	78	GRAY CLAY & SHALE			
78	80	HARD GRAY SHALE & GYPSUM			

7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9 / 7 / 02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 397 This Water Well Record was completed on (mo/day/yr) 9 / 9 / 02 under the business name of CENTRAL KANSAS DRILLING by (signature) Arnold R. Martin