

1 LOCATION OF WATER WELL: County: <u>Dickinson</u>	Fraction <u>SW 1/4 SE 1/4 SE 1/4</u>	Section Number <u>33</u>	Township Number <u>T 14 S</u>	Range Number <u>R 2 E/W</u>
---	---	-----------------------------	----------------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?
10 miles South of Abilene, Ks to 1300 Ave & 3/4 miles to 981 - 1300 Ave

2 WATER WELL OWNER: Duane Beemer
 RR#, St. Address, Box # : 981 - 1300 Ave
 City, State, ZIP Code : Abilene, Kansas 67410
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL <u>54</u> ft. ELEVATION:
--	--

Depth(s) Groundwater Encountered 1, 3, 6 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL 22 ft. below land surface measured on 7 / 19 / 03

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 1.3 gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	<u>7 Domestic (lawn & garden)</u>
		9 Dewatering
		12 Other (Specify below)
		10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No*; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes * No

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued* Clamped
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
		7 Fiberglass		Threaded

Blank casing diameter 5 in. to 54 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 48 in., weight 200 lbs./ft. Wall thickness or guage No. 250

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless Steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-Cement
2 Brass	4 Galvanized Steel	6 Concrete tile	9 ABS	11 Other (Specify)
				12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	<u>3 Mill slot</u>	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	ft.

SCREEN-PERFORATED INTERVALS: From 31 ft. to 54 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 23 ft. to 54 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 2 ft. to 23 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
<u>2 Sewer lines</u>	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? SOUTHWEST APPROX How many feet? 340

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	DARK TOP SOIL			
1	8	BROWN CLAY			
8	25	LITE COLOR SOFT CLAY			
25	27	BROWN ROCK HONEYCOMB SANDY			
27	33	TAN CLAY			
33	36	GRAY CLAY & SHALE			
36	48	GRAY SHALE & SOME GYPSUM ROCK			
48	50	DARK BROWN ROCK			
50	54	GRAY SHALE & GYPSUM ROCK			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7 / 19 / 03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 397 This Water Well Record was completed on (mo/day/yr) 7 / 25 / 03 under the business name of CENTRAL KANSAS DRILLING by (signature) Hubert D. Martin