

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Dickinson</u>	<u>SE 1/4 SW 1/4 SE 1/4</u>	<u>30</u>	<u>T 14 S</u>	<u>R 2 E/W*</u>

Distance and direction from nearest town or city street address of well if located within city?
8 miles South of Abilene, Ks on Hwy 15 to 1400 Ave & 1 1/4 miles West to 769 - 1400 Av

2 WATER WELL OWNER: Eric Stubbs
 RR#, St. Address, Box # : 769 - 1400 Ave
 City, State, ZIP Code : Abilene, Kansas 67410
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
W			E
		*	
			S

4 DEPTH OF COMPLETED WELL 6.0 ft. ELEVATION:

Depth(s) Groundwater Encountered 1 4.1 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 3.8 ft. below land surface measured on mo/day/yr 3 / 14 / 05
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 1.5 gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well
 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No * ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes * No

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued * Clamped
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
		7 Fiberglass		Threaded

Blank casing diameter 5 in. to 6.0 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 1.2 in., weight 2.00 lbs./ft. Wall thickness or gauge No. 2.50

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless Steel	5 Fiberglass	7 PVC	10 Asbestos-Cement
2 Brass	4 Galvanized Steel	6 Concrete tile	8 RMP (SR)	11 Other (Specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	ft.

SCREEN-PERFORATED INTERVALS: From 3.8 ft. to 6.0 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 2.3 ft. to 6.0 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout intervals: From 3 ft. to 2.3 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? EAST APPROX How many feet? 175

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	9	DARK CLAY			
9	11	BROWN CLAY			
11	30	LITE COLOR SHALEY CLAY			
30	31	TAN & LITE GRAY CLAY			
31	33	LITE COLOR SHALEY CLAY			
33	35	SOFT SHALEY LIMESTONE			
35	39	SOFT LITE COLOR CLAY			
39	41	LITE COLOR SHALE			
41	53	SOFT TAN CLAY			
53	60	GRAY SOFT CLAY & SHALE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3 / 14 / 05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 39.7 This Water Well Record was completed on (mo/day/yr) 3 / 20 / 05 under the business name of CENTRAL KANSAS DRILLING by (signature) Harold D. Martin