


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: JOHNSON		Fraction SE 1/4 SW 1/4 SE 1/4	Section Number 1	Township Number T 14 S	Range Number R 21 E
Distance and direction from nearest town or city street address of well if located within city? 37824 W 151st Eudora, KS 6 miles SE of Eudora, KS 38°51.4' 95°15'					
2 WATER WELL OWNER: James Peterson RR#, St. Address, Box #: 420 E Mill City, State, ZIP Code: Osawatomie, KS 66064		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 120 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 40 ft. 2. 40 ft. 3. 40 ft. WELL'S STATIC WATER LEVEL 40 ft. below land surface measured on mo/day/yr Pump test data: Well water was 45 ft. after 8 hours pumping 120 gpm Est. Yield 2 gpm: Well water was 45 ft. after 8 hours pumping 120 gpm Bore Hole Diameter 18 in. to 45 ft. and 8 in. to 120 ft. WELL WATER TO BE USED AS: <input checked="" type="checkbox"/> 1 Domestic <input type="checkbox"/> 3 Feedlot <input type="checkbox"/> 6 Oil field water supply <input type="checkbox"/> 9 Dewatering <input type="checkbox"/> 12 Other (Specify below) <input type="checkbox"/> 2 Irrigation <input type="checkbox"/> 4 Industrial <input type="checkbox"/> 7 Lawn and garden only <input type="checkbox"/> 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No			
5 TYPE OF BLANK CASING USED: 1 Steel <input type="checkbox"/> 3 RMP (SR) <input type="checkbox"/> 5 Wrought iron <input type="checkbox"/> 8 Concrete tile <input type="checkbox"/> CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped <input type="checkbox"/> <input checked="" type="checkbox"/> 2 PVC <input type="checkbox"/> 4 ABS <input type="checkbox"/> 6 Asbestos-Cement <input type="checkbox"/> 9 Other (specify below) <input type="checkbox"/> Welded <input type="checkbox"/> Blank casing diameter 5 in. to 120 ft., Dia 120 in. to 120 ft., Dia 120 in. to 120 ft. Casing height above land surface 24 in., weight 24 lbs./ft. Wall thickness or gauge No. SPR26 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel <input type="checkbox"/> 3 Stainless steel <input type="checkbox"/> 5 Fiberglass <input type="checkbox"/> 8 RMP (SR) <input type="checkbox"/> 10 Asbestos-cement <input type="checkbox"/> 2 Brass <input type="checkbox"/> 4 Galvanized steel <input type="checkbox"/> 6 Concrete tile <input type="checkbox"/> 9 ABS <input type="checkbox"/> 11 Other (specify) <input type="checkbox"/> 12 None used (open hole) <input type="checkbox"/> SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot <input type="checkbox"/> 3 Mill slot <input type="checkbox"/> 5 Gauzed wrapped <input type="checkbox"/> 8 Saw cut <input type="checkbox"/> 11 None (open hole) <input type="checkbox"/> 2 Louvered shutter <input type="checkbox"/> 4 Key punched <input type="checkbox"/> 6 Wire wrapped <input checked="" type="checkbox"/> 9 Drilled holes <input type="checkbox"/> 10 Other (specify) <input type="checkbox"/> SCREEN-PERFORATED INTERVALS: From 40 ft. to 45 ft. From 40 ft. to 45 ft. From 40 ft. to 45 ft. GRAVEL PACK INTERVALS: From 37 ft. to 120 ft. From 37 ft. to 120 ft. From 37 ft. to 120 ft.					
6 GROUT MATERIAL: <input checked="" type="checkbox"/> 1 Neat cement <input type="checkbox"/> 2 Cement grout <input type="checkbox"/> 3 Bentonite <input type="checkbox"/> 4 Other <input type="checkbox"/> Grout Intervals: From 17 ft. to 37 ft. From 17 ft. to 37 ft. From 17 ft. to 37 ft. What is the nearest source of possible contamination: <input checked="" type="checkbox"/> 1 Septic tank Future <input type="checkbox"/> 4 Lateral lines <input type="checkbox"/> 7 Pit privy <input type="checkbox"/> 10 Livestock pens <input type="checkbox"/> 14 Abandoned water well <input type="checkbox"/> 2 Sewer lines <input type="checkbox"/> 5 Cess pool <input type="checkbox"/> 8 Sewage lagoon <input type="checkbox"/> 11 Fuel storage <input type="checkbox"/> 15 Oil well/Gas well <input type="checkbox"/> 3 Watertight sewer lines <input type="checkbox"/> 6 Seepage pit <input type="checkbox"/> 9 Feedyard <input type="checkbox"/> 12 Fertilizer storage <input type="checkbox"/> 16 Other (specify below) 13 Insecticide storage <input type="checkbox"/> Direction from well? NE Future Septic How many feet? 150' when installed					
FROM		TO		LITHOLOGIC LOG	
0		2		Surface	
2		30		Clay	
30		40		Sandy clay	
40		46		Very sandy	
46		51		Limestone	
51		66		Shale	
66		78		Shale Black	
78		85		Limestone	
85		90		Shale	
90		91		Limestone	
91		96		Shale	
96		115		Limestone	
115		120		Shale	
FROM		TO		PLUGGING INTERVALS	
0		2			
2		30			
30		40			
40		46			
46		51			
51		66			
66		78			
78		85			
85		90			
90		91			
91		96			
96		115			
115		120			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-29-98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 240 This Water Well Record was completed on (mo/day/yr) 5-31-98 under the business name of FE Young Drilling Co. by (signature) Edward Young					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4