Constitution Controller Controller Controller	Vell ID
	T = 1.
1 LOCATION OF WATER WELL: Fraction Section Number Township Number SE <sup>1</sup> / <sub>4</sub> SW <sup>1</sup> / <sub>4</sub> SW <sup>1</sup> / <sub>4</sub> SE <sup>1</sup> / <sub>4</sub> SW <sup>1</sup> / <sub>4</sub> SE <sup>1</sup> / <sub>4</sub> S	Range Number R 21 ■ E □ W
2 WELL OWNER: Last Name: Shuey First: Kim Business:  Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here:	
Address: 2100' West of intersection of N 300 Rd & F 2300 Rd. Edgerton.	
City: Wellsville State: KS ZIP: 66092 KS. The property is on the N side of N 300 Rd.	
3 LOCATE WELL WITH "X" IN 4 DEPTH OF COMPLETED WELL: 200	
SECTION ROY: Depth(s) Groundwater Encountered: 1)	
2)	
below land surface, measured on (mo-day-yr)	
NW NE	es 🗌 No)
Pump test data: Well water was	
Well water was ft.	
SW SE after hours pumping	Ground Level □ TOC
S Bore Hole Digmeter: 5 625 in to 200 ft and Source: \( \tau\) Land Survey \( \tau\) GPS	S   Topographic Map
1 mile  Other KOLAR	,
7 WELL WATER TO BE USED AS:	
1. Domestic: 5. ☐ Public Water Supply: well ID	
Household 6. ☐ Dewatering: how many wells?	
☐ Livestock 8. ☐ Monitoring: well ID	•••••
2. Irrigation 9. Environmental Remediation: well ID	
3.	
Was a chemical/bacteriological sample submitted to KDHE?  \( \subseteq \text{Yes} \subseteq \text{No} \) If yes, date sample was submitted:	
Water well disinfected?  No	
8 TYPE OF CASING USED: ☐ Steel ☐ PVC ☐ Other	
Casing diameter in. to	
Casing height above land surface in. Weight lbs./ft. Wall thickness or gauge No	
TYPE OF SCREEN OR PERFORATION MATERIAL:         □ Steel       □ Stainless Steel       □ PVC       □ Other (Specify)	
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	
☐ Continuous Slot ☐ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)	
□ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole)  SCREEN-PERFORATED INTERVALS: From	
GRAVEL PACK INTERVALS: From	
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other	
Grout Intervals: From 200 ft. to 0 ft., From ft. to ft., From ft. to ft.	
Nearest source of possible contamination:   □ Septic Tank □ Lateral Lines □ Pit Privy □ Livestock Pens □ Insecticide Storage	
☐ Sewer Lines ☐ Cess Pool ☐ Sewage Lagoon ☐ Fuel Storage ☐ Abandone	
☐ Watertight Sewer Lines ☐ Seepage Pit ☐ Feedyard ☐ Fertilizer Storage ☐ Oil Well/C	
☐ Other (Specify)	
10 FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG (cont.) or PI	LUGGING INTERVALS
0 4 SOIL & CLAY 154 166 LIME	
4 12 SANDSTONE 166 170 SHALE	
12 118 SHALE 170 179 LIME	
118 126 LIME 179 180 SHALE	
126         129         SHALE         180         190         LIME           129         130         LIME         190         200         SHALE	
130 132 SHALE Notes:	
132 147 LIME	
147 154 SHALE	
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, recons	tructed, or plugged
under my jurisdiction and was completed on (mo-day-year) .06/18/2020 and this record is true to the best of my k Kansas Water Well Contractor's License No. 953 This Water Well Record was completed on Ano-day-year	(110 wiedge and benef. -) 06/23/2020
under the business name of Allens Holdings & Investments dba EED Signature	
Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water	r, GWTS Section,
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone Visit us at http://www.kdheks.gov/waterwell/index.html  KSA 82a-1212	e /85-296-5524. Revised 7/10/2015