


1 LOCATION OF WATER WELL: County: JOHNSON	Fraction SW 1/4 SW 1/4 NW 1/4	Section Number 1	Township Number T 14 S	Range Number R 23 EW
--	----------------------------------	---------------------	---------------------------	-------------------------

Distance and direction from nearest town or city street address of well if located within city?

1400 S HARRISON ST OLAHE, KS

MW-7

2 WATER WELL OWNER: WITCO CORPORATION RR#, St. Address, Box # : 1400 S HARRISON ST City, State, ZIP Code : OLAHE, KANSAS 66061	Board of Agriculture, Division of Water Resources Application Number:
--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL 49.25 ft. ELEVATION: 1009.53 Depth(s) Groundwater Encountered 1. 33.24 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 33.24 ft. below land surface measured on mo/day/yr 08/04/96 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter .8 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
---	--

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter 2 in. to 24.25 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface -5 in. weight 0.70 lbs./ft. Wall thickness or gauge No. SCH. 40	5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass Casing JOINTS: Glued Clamped Welded Threaded X
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 0.010 IN 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 24.25 ft. to 49.25 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 22.25 ft. to 49.25 ft. From ft. to ft.	10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 10 Other (specify)

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 20.25 ft. From 20.25 ft. to 22.25 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? W How many feet? 30	13 Insecticide storage LUBE OIL STORAGE
--	--

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	10	GRAY BROWN SILTY SANDY CLAY			
10	15	DARK GRAY-BLACK AND BROWN SILTY CLAY (FILL)			
15	20	DARK GRAY BROWN CLAY			
20	35	TAN BROWN SILTY CLAY			
35	40	TAN-BROWN CLAY			
40	53	TAN - GRAY BROWN CLAY (SHALEY)			
		AUGER REFUSAL AT 53 FEET ON LIMESTONE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08/01/96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 102 This Water Well Record was completed on (mo/day/yr) under the business name of LAYNE-WESTERN by (signature)
--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.