

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

<input checked="" type="checkbox"/> Location of well:		County Johnson	Fraction NW 1/4 SE 1/4 SE 1/4	Section number 34	Township number 14	Range number S R 23																																																						
2. Distance and direction from nearest town or city: 1/2 mi. West of Ocheltree, Ks. Street address of well location if in city:			3. Owner of well: Patrick F. Long R.R. or street: P 8010 W. Country Club Apt. 4 City, state, zip code: Overland Park, Kans 66106																																																									
4. Locate with "X" in section below: 			6. Bore hole dia. 8 1/2 in. Completion date 9-28-76 Well depth 130 ft.																																																									
5. Type and color of material			7. <input checked="" type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary																																																									
<table border="1"> <thead> <tr> <th>From</th> <th>To</th> <th>Material</th> </tr> </thead> <tbody> <tr><td>0</td><td>3</td><td>surface</td></tr> <tr><td>3</td><td>5</td><td>Clay yellow</td></tr> <tr><td>5</td><td>6</td><td>Broken rock</td></tr> <tr><td>6</td><td>9</td><td>clay yellow</td></tr> <tr><td>9</td><td>11</td><td>Broken rock</td></tr> <tr><td>11</td><td>14</td><td>clay yellow</td></tr> <tr><td>14</td><td>15</td><td>lime gray</td></tr> <tr><td>15</td><td>22</td><td>shale gray</td></tr> <tr><td>22</td><td>24</td><td>black slate</td></tr> <tr><td>24</td><td>31</td><td>lime gray</td></tr> <tr><td>31</td><td>39</td><td>shale gray</td></tr> <tr><td>39</td><td>54</td><td>lime gray</td></tr> <tr><td>54</td><td>59</td><td>shale gray</td></tr> <tr><td>59</td><td>62</td><td>red bed</td></tr> <tr><td>62</td><td>79</td><td>shale gray</td></tr> <tr><td>79</td><td>87</td><td>lime gray</td></tr> <tr><td>87</td><td>130</td><td>shale gray</td></tr> </tbody> </table>			From	To	Material	0	3	surface	3	5	Clay yellow	5	6	Broken rock	6	9	clay yellow	9	11	Broken rock	11	14	clay yellow	14	15	lime gray	15	22	shale gray	22	24	black slate	24	31	lime gray	31	39	shale gray	39	54	lime gray	54	59	shale gray	59	62	red bed	62	79	shale gray	79	87	lime gray	87	130	shale gray	8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other			
From	To	Material																																																										
0	3	surface																																																										
3	5	Clay yellow																																																										
5	6	Broken rock																																																										
6	9	clay yellow																																																										
9	11	Broken rock																																																										
11	14	clay yellow																																																										
14	15	lime gray																																																										
15	22	shale gray																																																										
22	24	black slate																																																										
24	31	lime gray																																																										
31	39	shale gray																																																										
39	54	lime gray																																																										
54	59	shale gray																																																										
59	62	red bed																																																										
62	79	shale gray																																																										
79	87	lime gray																																																										
87	130	shale gray																																																										
18. Elevation: 1040 1038 Topography: <input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley			9. Casing: Material RMP Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input checked="" type="checkbox"/> PVC <input type="checkbox"/> Weight 1 1/2 lbs./ft. Dia. 5 in. to 130 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 1/4																																																									
19. Remarks: Customer is aware of State regulation and agrees to install a 4' square re-enforced concrete platform around top of well. X P.F. Long			10. Screen: Manufacturer's name Pioneer Mfg. Co. Type RPM Dia. 5" Slot/gauze see note Length 110' Set between 20 ft. and 130 ft. ft. and <input type="checkbox"/> ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 1/4" / 8																																																									
20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. E. Young Drilling 240 Business name 6355 Robinhood Merriam License No. _____ Address KS Signed E. Young Date 3-30-76 Authorized representative																																																												

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-3

Note: Slot size. All casing perforated with 3/32 drill from bottom of well.
 To 20'

8/92
 17
 33
 34
 Sec
 1/4 1/4 1/4