

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL:

County: Johnson

Fraction

SE 1/4 NW 1/4 SE 1/4

Section Number

34

Township Number

T 14 S

Range Number

R 23 EW

Distance and direction from nearest town or city street address of well if located within city?

1 mile NW of Spring Hill

Global Positioning Systems (decimal degrees, min. of 4 digits)

Latitude: N38°47'08.8"Longitude: W94°50'20.8"Elevation: 11014Datum: NAD 27Data Collection Method: Hand GPS

2 WATER WELL OWNER:

RR#, St. Address, Box #

City, State, ZIP Code


Douglas Brandt21940 W 191st St.Spring Hill KS 66083

3 LOCATE WELL'S

LOCATION

WITH AN "X" IN SECTION BOX:

N



S

4 DEPTH OF COMPLETED WELL 150 ft.Depth(s) Groundwater Encountered (1) 130 ft. (2) ft. (3) ft.WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr.

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield: 4.5 gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrSample was submitted Water well disinfected? Yes X No

5 TYPE OF CASING USED:

1 Steel 3 RMP (SR)

2 PVC 4 ABS

5 Wrought Iron

6 Asbestos-Cement

7 Fiberglass

8 Concrete tile

9 Other (specify below)

CASING JOINTS: Glued Clamped

Welded

Threaded

Blank casing diameter 5 in. to ft., Diameter in. to ft., Diameter in. to ft.

Casing height above land surface in., Weight lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless Steel

5 Fiberglass

7 PVC

9 ABS

11 Other (Specify)

2 Brass 4 Galvanized Steel

6 Concrete tile

8 RM (SR)

10 Asbestos-Cement

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot

5 Gauzed wrapped

7 Torch cut

9 Drilled holes

11 None (open hole)

2 Louvered shutter 4 Key punched

6 Wire wrapped

8 Saw cut

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 120 ft. to 140 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 23 ft. to 150 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

6 GROUT MATERIAL:

1 Neat cement

2 Cement grout

3 Bentonite

4 Other

Grout Intervals: From 0 ft. to 23 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

13 Insecticide storage

16 Other (specify

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

14 Abandoned water well

below)

3 Watertight sewer lines

6 Seepage pit

9 Feedyard

12 Fertilizer storage

15 Oil well/gas well

plugged

Direction from well?

How many feet? 50' water well

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Clay			
5	14	Limestone			
14	25	Shale			
25	31	Limestone			
31	39	Shale			
39	54	Limestone			
54	79	Shale			
79	87	Limestone			
87	130	Shale			
130	156	Sandstone			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/13/09 and this record is true to the best of my knowledge and belief.Kansas Water Well Contractor's License No. 595 This Water Well Record was completed on (mo/day/year) 4/3/09under the business name of Jessie KumWell Drilling by (signature) Jessie KumWell

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at <http://www.kdheks.gov/waterwell/index.html>.