


1 LOCATION OF WATER WELL: County: Johnson		Fraction NE 1/4 NE 1/4 NE 1/4		Section Number 12		Township Number T 14 S		Range Number R 23 EW	
Distance and direction from nearest town or city street address of well if located within city? 1805 S. Ridgeview, Olathe, KS.									
2 WATER WELL OWNER: Criswell Petroleum Products RR#, St. Address, Box # : 916 S. 9th City, State, ZIP Code : St. Joseph, MO. 64503 Board of Agriculture, Division of Water Resources Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 			4 DEPTH OF COMPLETED WELL: 25' ft. ELEVATION: Depth(s) Groundwater Encountered 1. 18' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 3' 6 1/2" ft. below land surface measured on mo/day/yr 3-18-95 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 1/2" - 25' ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No						
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2.375 in. to 15' ft., Dia. in. to ft., Dia. in. to SDR 13 ft. Casing height above land surface Flush Mount in., weight lbs./ft. Wall thickness or gauge No. SCH 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 25' ft. to 15' ft., From ft. to ft. GRAVEL PACK INTERVALS: From 25' ft. to 13' ft., From ft. to ft. From ft. to ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 13' ft. to 3' ft., From 3' ft. to 0' ft., From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? west How many feet? 10'									
FROM TO LITHOLOGIC LOG					FROM TO PLUGGING INTERVALS				
0 .75 Asphalt									
.75 4.75 Gray-green mottled clay, iron oxides, plastic firm, ropey.									
4.75 19 Gray mottled clay w/iron oxide staining, tight, no odor, plastic.									
19 21.50 Yellow brn clay w/ ls rx. gravel, moist.									
21.50 25 Dry olive gray shale, firm, no odor.									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-8-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 3-26-95 under the business name of JB Environmental Drilling by (signature) James Bieker									