

1 LOCATION OF WATER WELL: County: Johnson	Fraction NE 1/4 NE 1/4 NE 1/4	Section Number 12	Township Number T 14 S	Range Number R 23 EW
---	---	-----------------------------	----------------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1805 S. Ridgeview, Olathe, KS.

2 WATER WELL OWNER: RR#, St. Address, Box # City, State, ZIP Code	Criswell Petroleum Products 916 S. 9th St. Joseph, MO. 64503	Board of Agriculture, Division of Water Resources Application Number:
---	---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 25' ft. ELEVATION: 3-18-95 ft.
	Depth(s) Groundwater Encountered 1. 19' ft. 2. 4' 6 1/2" ft. 3. 3-18-95 ft. WELL'S STATIC WATER LEVEL 4' 6 1/2" ft. below land surface measured on mo/day/yr Pump test data: Well water was 25' ft. after 3-18-95 hours pumping 3-18-95 gpm Est. Yield 3 1/2" gpm: Well water was 25' ft. after 3-18-95 hours pumping 3-18-95 gpm Bore Hole Diameter 8 1/2" in. to 25' ft., and 25' in. to 25' ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded X	2 PVC 4 ABS 7 Fiberglass Threaded X
Blank casing diameter 2 3/4 in. to 15' ft. Dia 15' in. to 15' ft. Dia 15' in. to 15' ft.	Casing height above land surface Flush Mount weight 15' lbs./ft. Wall thickness or gauge No. SDR 13
TYPE OF SCREEN OR PERFORATION MATERIAL:	10 Asbestos-cement 11 Other (specify) SCH 40
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 25' ft. to 15' ft. From 15' ft. to 15' ft.
GRAVEL PACK INTERVALS:	From 25' ft. to 15' ft. From 15' ft. to 15' ft.

6 GROUT MATERIAL:	1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 12 1/2' ft. to 3' ft. From 3' ft. to 0' ft. From 0' ft. to 0' ft.	
What is the nearest source of possible contamination:	10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well	2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage	
Direction from well? Northwest	How many feet? 70'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.75	Asphalt w/ ls rx.gravel			
.75	2	Green-greenish gray mottled clay, tight, moist.			
2	14.50	gray clay, tight, mottled w/ iron oxides & dk gray-blk stringers (roots casts) no odor.			
14.50	21	Grayish brn-yellowish gray tight clay w/ ls.rx. gravel, caliche, moist, no odor.			
21	25	yellow brn-olive shale, dry, no odor.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-8-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 3-26-95 under the business name of JB Environmental Drilling by (signature) James Baker
