

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number
County: Johnson	NE ¼ NE ¼ NW ¼	15	T 14 S R 24 E
Distance and direction from nearest town or city street address of well if located within city? 159 th & Mission Rd. in Overland Park, KS 60 east from intersection approx. 1,000 ft on south side of road			
2 WATER WELL OWNER: The Williams Companies RR#, St. Address, Box # : One William Center City, State, ZIP Code : Tulsa, OK 74172 Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL 20 ft. ELEVATION: - ft. Depth(s) Groundwater Encountered 1 19 ft. 2 - ft. 3 - ft. WELL'S STATIC WATER LEVEL 8.67 ft. below land surface measured on mo/day/yr 11/24/05 Pump test data: Well water was - ft. after - hours pumping - gpm Est. Yield - gpm: Well water was - ft. after - hours pumping - gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) ⑩ Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No ☒ ; If yes, mo/day/yrs sample was submitted Water Well Disinfected? Yes No ☒		
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped ⑥ PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded Threaded ☒ Blank casing diameter 2 in. to ft., Dia - in. to ft., Dia - in. to ft. Casing height above land surface 24 in., weight lbs./ft. Wall thickness or gauge No. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass ⑧ PVC 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot ⑨ Mill slot 5 Guazed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) ft. SCREEN-PERFORATED INTERVALS: From 20 ft. to 5 ft., From - ft. to - ft. GRAVEL PACK INTERVALS: From 20 ft. to 4 ft., From - ft. to - ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout ③ Bentonite 4 Other Grout Intervals: From 4 ft. to 2 ft., From - ft. to - ft., From - ft. to - ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy ① Fuel storage - former 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below) Direction from well? North How many feet? 1,000 +			
FROM	TO	LITHOLOGIC LOG	FROM TO PLUGGING INTERVALS
0	1	Topsoil, Dark Brown	
1	12.5	Silty Clay, light brown, stiff, moist	
12.5	20	Clay, gray, stiff, wet	
20	-	Gray shale	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/24/05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 710 This Water Well Record was completed on (mo/day/yr) 2/16/05 by signature [Signature]			
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.			