

1 LOCATION OF WATER WELL: County: <u>JOHNSON</u>		Fraction: <u>SE 1/4 SE 1/4 SE 1/4</u>		Section Number: <u>6</u>		Township Number: <u>T 14 S</u>		Range Number: <u>R 25 EW</u>																																					
Distance and direction from nearest town or city street address of well if located within city? <u>151st & METCALF</u>																																													
2 WATER WELL OWNER: <u>SUBURBAN TIRE & AUTO</u> RR#, St. Address, Box #: <u>151st & METCALF</u> City, State, ZIP Code: <u>STANLEY, KS 6</u>						mw # <u>2</u> Board of Agriculture, Division of Water Resources Application Number:																																							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 			4 DEPTH OF COMPLETED WELL: <u>21</u> ft. ELEVATION: <u>998.92</u> Depth(s) Groundwater Encountered 1. <u>9</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>9</u> ft. below land surface measured on mo/day/yr <u>6/22/94</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>8</u> in. to <u>21</u> ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10</u> Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <u>X</u>																																										
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped <u>2</u> PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>2</u> in. to <u>10.5</u> ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface <u>0</u> in., weight lbs./ft. Wall thickness or gauge No. <u>SCH 40</u> TYPE OF SCREEN OR PERFORATION MATERIAL: <u>1</u> PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped <u>8</u> Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From <u>10.5</u> ft. to <u>21</u> ft., From ft. to ft. GRAVEL PACK INTERVALS: From <u>9</u> ft. to <u>21</u> ft., From ft. to ft. From ft. to ft., From ft. to ft.																																													
6 GROUT MATERIAL: <u>1</u> Neat cement 2 Cement grout <u>3</u> Bentonite 4 Other Grout Intervals: From <u>1</u> ft. to <u>0</u> ft., From <u>1</u> ft. to <u>9</u> ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy <u>11</u> Fuel storage 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below) Direction from well? <u>AT SITE - ABANDONED</u> How many feet?																																													
<table border="1"><thead><tr><th>FROM</th><th>TO</th><th>LITHOLOGIC LOG</th><th>FROM</th><th>TO</th><th>PLUGGING INTERVALS</th></tr></thead><tbody><tr><td><u>0</u></td><td><u>1</u></td><td><u>GRAVEL SURFACE</u></td><td></td><td></td><td></td></tr><tr><td><u>1</u></td><td><u>5</u></td><td><u>STIFF SILTY CLAY, OR-BRN</u></td><td></td><td></td><td></td></tr><tr><td><u>5</u></td><td><u>6</u></td><td><u>SANDY SILTY CLAY, OR-YEL</u></td><td></td><td></td><td></td></tr><tr><td><u>6</u></td><td><u>90</u></td><td><u>SILTY SAND, FGR- OR-BRN</u></td><td></td><td></td><td></td></tr><tr><td><u>10</u></td><td><u>21</u></td><td><u>SANDSTONE, FGR-BRN</u></td><td></td><td></td><td></td></tr></tbody></table>										FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	<u>0</u>	<u>1</u>	<u>GRAVEL SURFACE</u>				<u>1</u>	<u>5</u>	<u>STIFF SILTY CLAY, OR-BRN</u>				<u>5</u>	<u>6</u>	<u>SANDY SILTY CLAY, OR-YEL</u>				<u>6</u>	<u>90</u>	<u>SILTY SAND, FGR- OR-BRN</u>				<u>10</u>	<u>21</u>	<u>SANDSTONE, FGR-BRN</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																								
<u>0</u>	<u>1</u>	<u>GRAVEL SURFACE</u>																																											
<u>1</u>	<u>5</u>	<u>STIFF SILTY CLAY, OR-BRN</u>																																											
<u>5</u>	<u>6</u>	<u>SANDY SILTY CLAY, OR-YEL</u>																																											
<u>6</u>	<u>90</u>	<u>SILTY SAND, FGR- OR-BRN</u>																																											
<u>10</u>	<u>21</u>	<u>SANDSTONE, FGR-BRN</u>																																											
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>1</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6/22/94</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>554</u> This Water Well Record was completed on (mo/day/yr) <u>7/25/94</u> under the business name of <u>AGD SERVICES</u> by (signature) <u>Keith Pearson Sec/300</u>																																													