

MW-1D

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Johnson</u>	<u>SE</u> $\frac{1}{4}$ <u>NW</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$	<u>18</u>	T <u>14</u> S	R <u>25</u> <u>EW</u>

Distance and direction from nearest town or city street address of well if located within city?

7100 W. 167th St.

2 WATER WELL OWNER:	RR#, St. Address, Box #	City, State, ZIP Code	Board of Agriculture, Division of Water Resources Application Number:
<u>APAC-KS</u>	<u>7100 W 167th St</u>	<u>Overland Park KS 66283</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	ELEVATION:
	<u>96.4</u> ft.	<u>963.4</u> ft.
	Depth(s) Groundwater Encountered 1 <u>NOT ENCOUNTERED</u> ft. 3 <u>NOT ENCOUNTERED</u> ft.	
	WELL'S STATIC WATER LEVEL <u>90.1</u> ft. below land surface measured on mo/day/yr <u>12/15/2005</u>	
	Pump test data: Well water was <u>NA</u> ft. after <u>NA</u> hours pumping <u>NA</u> gpm	
	Est. Yield <u>NA</u> gpm: Well water was <u>NA</u> ft. after <u>NA</u> hours pumping <u>NA</u> gpm	
	WELL WATER TO BE USED AS:	
	5 Public water supply 8 Air conditioning 11 Injection well	
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
	2 Irrigation 4 Industrial 7 Domestic (lawn & garden) <u>10</u> Monitoring well	
	Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> <u>X</u> ; If yes, mo/day/yr sample was submitted	
	Water Well Disinfected? Yes <u>No</u>	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>Clamped</u>
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded <u>Threaded</u> <u>X</u>
<u>2</u> PVC	7 Fiberglass		
3 RMP (SR)			
4 ABS			
Blank casing diameter <u>6</u> in. to <u>8.2</u> ft., Dia <u>2</u> in. to <u>86.2</u> ft., Dia <u>NA</u> in. to <u>NA</u> ft.			
Casing height above land surface <u>1.72</u> ft. in., weight <u>NA</u> lbs./ft. Wall thickness or gauge No. <u>sch 40</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:	<u>7</u> PVC	10 Asbestos-Cement	
1 Steel	8 RMP (SR)	11 Other (Specify)	
2 Brass	9 ABS	12 None used (open hole)	
3 Stainless Steel			
4 Galvanized Steel			
5 Fiberglass			
6 Concrete tile			
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
<u>1</u> Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS:	From <u>86.2</u> ft. to <u>96.2</u> ft., From <u>NA</u> ft. to <u>NA</u> ft.		
GRAVEL PACK INTERVALS:	From <u>96.4</u> ft. to <u>83.5</u> ft., From <u>NA</u> ft. to <u>NA</u> ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	<u>3</u> Bentonite	4 Other <u>high solids bent slurry</u>
Grout intervals:	From <u>83.5</u> ft. to <u>79</u> ft.	From <u>79</u> ft. to <u>95.3</u> ft.	From <u>82</u> ft. to <u>95.3</u> ft.	
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	<u>16</u> Other (specify below)
Direction from well? <u>South</u>			13 Insecticide storage	<u>landfill C+D</u>
			How many feet? <u>~650</u>	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	34	clay			
34	61	shale			
61	62	limestone			
62	63	shale			
63	66	limestone			
66	68	shale			
68	80	limestone			
80	82	shale			
82	84	limestone			
84	87	shale			
87	93	limestone			
93	95	shale			
95	96.5	limestone			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>12/5/05</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <u>760</u> This Water Well Record was completed on (mo/day/yr) <u>12/7/06</u> under the business name of <u>ASSOCIATED DRILLING INC</u> by (signature) <u>[Signature]</u>
