


1 LOCATION OF WATER WELL: County: Johnson Fraction: SE 1/4 SE 1/4 SE 1/4 Section Number: 18 Township Number: T 14 S Range Number: R 25 EW

Distance and direction from nearest town or city street address of well if located within city? 7100 W. 167th St

2 WATER WELL OWNER: APAC-KS RR#, St. Address, Box #: 7100 W. 167th City, State, ZIP Code: Orland Park KS 66283 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 23.2 ft. ELEVATION: NE

Depth(s) Groundwater Encountered: 1 1 ft. 2 NE ft. 3 1/14/06 ft.
 WELL'S STATIC WATER LEVEL: 24.8 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was NA ft. after NA hours pumping NA gpm
 Est. Yield: NA gpm; Well water was NA ft. after NA hours pumping NA gpm
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes NA No NA

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued NA Clamped NA
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded NA
 7 Fiberglass Threaded X

Blank casing diameter: 2" in. to 13 ft., Dia NA in. to NA ft., Dia NA in. to NA ft.
 Casing height above land surface: 2.29 in., weight NA lbs./ft. Wall thickness or gauge No. 240

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify) NA
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes 10 Other (specify) NA ft.

SCREEN-PERFORATED INTERVALS: From 13 ft. to 23 ft., From NA ft. to NA ft.
 GRAVEL PACK INTERVALS: From 10 ft. to 27.5 ft., From NA ft. to NA ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite dry Other NA

Grout Intervals: From 10 ft. to 1 ft., From NA ft. to NA ft., From NA ft. to NA ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) CT Island Hill
 13 Insecticide storage

Direction from well? NW How many feet? 150

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	clay			
2	4	limestone			
4	14	limestone weathered slightly			
14	22	shale limestone			
22	27.5	shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-2-07 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 760 This Water Well Record was completed on (mo/day/yr) 1/27/06 under the business name of ASSOLEATED DRILLING INC. by (signature) [Signature]