

MW-09

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Johnson</u>	<u>SE 1/4 NE 1/4 SE 1/4</u>	<u>18</u>	T <u>14</u> S	R <u>25</u> E/W

Distance and direction from nearest town or city street address of well if located within city?

7100 W 167th St

2 WATER WELL OWNER:	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : <u>7100 W 167th</u>	Application Number:
City, State, ZIP Code : <u>Oreland Park KS 66283</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	ELEVATION:
	<u>100.23</u> ft.	<u>904.43</u>
	Depth(s) Groundwater Encountered 1 <u>NE</u> ft. 2 ft. 3 ft.	
	WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr	
	Pump test data: Well water was ft. after hours pumping gpm	
	Est. Yield gpm: Well water was ft. after hours pumping gpm	
	WELL WATER TO BE USED AS:	
	1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well	
	2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
	7 Domestic (lawn & garden) 10 Monitoring well	
	Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted	
	Water Well Disinfected? Yes No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	7 Fiberglass		Threaded
3 RMP (SR)			
4 ABS			
Blank casing diameter <u>6</u> in. to <u>86</u> ft., Dia <u>2</u> in. to <u>90</u> ft., Dia in. to ft.			
Casing height above land surface <u>2.77</u> ft. in., weight lbs./ft. Wall thickness or gauge No. <u>40</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-Cement	
1 Steel	8 RMP (SR)	11 Other (Specify)	
2 Brass	9 ABS	12 None used (open hole)	
3 Stainless Steel			
4 Galvanized Steel			
5 Fiberglass			
6 Concrete tile			
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS: From <u>90</u> ft. to <u>100</u> ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From <u>100</u> ft. to <u>88</u> ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other <u>high solids</u>
Grout Intervals: From <u>86-78 chips, 78 to surf + 2 bags - high solids</u> ft. to <u>88-82 chips, 82 to 2. high solids</u> ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	11 Fuel storage	15 Oil well/Gas well		
2 Sewer lines	12 Fertilizer storage	16 Other (specify below)		
3 Watertight sewer lines	13 Insecticide storage	<u>landfill 100ft west</u>		
4 Lateral lines				
5 Cess pool				
6 Seepage pit				
7 Pit privy				
8 Sewage lagoon				
9 Feedyard				
Direction from well?	How many feet?			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	27	Clay			
27	43	limestone			
43	45	shale			
45	60	limestone			
60	74	shale			
74	79.5	limestone			
79.5	80	shale			
80	82	limestone			
82	89	Chert shale - shale			
89	96	Chert shale - sandy silty shale			
96	100	Chert shale - shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>1-10-07</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <u>760</u> This Water Well Record was completed on (mo/day/yr) <u>2/10/07</u> under the business name of <u>Associated Agricultural Inc</u> by (signature) <u>[Signature]</u>
