

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL:

County: Johnson

Fraction

SW 1/4 SW 1/4 SE 1/4

Section Number

17

Township Number

T 14 S

Range Number

R 25 EW

Distance and direction from nearest town or city street address of well if located within city?


Global Positioning Systems (decimal degrees, min. of 4 digits)

Latitude: 38° 49' 31.6"Longitude: 94° 39' 03.6"Elevation: 910Datum: NAD 27Data Collection Method: GPS Hand Unit

2 WATER WELL OWNER:

RR#, St. Address, Box # : 5656 W 16th St.City, State, ZIP Code : Stillwell, KS. 66085

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL 150 ft.Depth(s) Groundwater Encountered (1) 140 ft. (2) ft. (3) ft.WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr.

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 4 gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrSample was submitted Water well disinfected? Yes X No

5 TYPE OF CASING USED:

1 Steel 3 RMP (SR)

5 Wrought Iron

6 Asbestos-Cement

8 Concrete tile

9 Other (specify below)

CASING JOINTS: Glued X Clamped

2 PVC 4 ABS

7 Fiberglass

Welded

Threaded

Blank casing diameter 5 in. to 120 ft., Diameter 5 in. to 150 ft., Diameter in. to ft.Casing height above land surface 12 in., Weight SDR 21 lbs./ft. Wall thickness or gauge No. 220 PSI

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel

3 Stainless Steel

5 Fiberglass

7 PVC

9 ABS

11 Other (Specify)

2 Brass

4 Galvanized Steel

6 Concrete tile

8 RM (SR)

10 Asbestos-Cement

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

2 Mill slot

5 Gauzed wrapped

7 Torch cut

9 Drilled holes

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

8 Saw Cut

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 120 ft. to 140 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 30 ft. to 150 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

6 GROUT MATERIAL:

1 Neat cement

2 Cement grout

3 Bentonite

4 Other

Grout Intervals: From 0 ft. to 30 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank

4 Lateral lines

Pit privy

10 Livestock pens

13 Insecticide Storage

16 Other (specify

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

14 Abandoned water well

below)

3 Watertight sewer lines

6 Seepage pit

9 Feedyard

12 Fertilizer Storage

15 Oil well/gas well

Direction from well? NEHow many feet? 150

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	7	Silty clay			
7	16	Shale			
16	26	Limestone			
26	42	Shale			
42	52	Limestone			
52	82	Shale			
82	90	Limestone			
90	140	Shale			
140	145	Benton sand			
145	150	Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/14/09 and this record is true to the best of my knowledge and belief.Kansas Water Well Contractor's License No. 595 This Water Well Record was completed on (mo/day/year) 4/8/08 under the business name of Jesse Yodum Well Drilling by (signature) Jesse YodumINSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at <http://www.kdheks.gov/waterwell/index.html>.