WATER WELL RECORD Form WWC-5 Division of Water												
Original Record Correction Change in Well Use						Resources App. No.				Well ID		
1 LOCATION OF WATER WELL: Fraction						Section Number Township Nu					nge Number	
County: Johnson SE <sup>1</sup> / <sub>4</sub> NW <sup>1</sup> / <sub>4</sub> SE <sup>1</sup> / <sub>4</sub>												
Business: Dee dir Address: 2542 Groonloof Court							Street or Rural Address where well is located (if unknown, distance and irection from nearest town or intersection): If at owner's address, check here: 4602 Cedar St eawood, KS 66224					
3 LOCAT						400 2 20.064526						
WITH "SECTION OF THE PROPERTY	WITH "X" IN SECTION BOX:  N  Depth(s) Groundwater Encountered: 1)						Tongitude:94.642352(decimal degrees) Horizontal Datum:					
11	S after hours pumping general stream after pumping series after series							6 Elevation:ft. ☐ Ground Level ☐ TOC Source: ☐ Land Survey ☐ GPS ☐ Topographic Map ☐ Other				
		O BE USED										
☐ House ☐ Lawn ☐ Livest  2. ☐ Irrigat  3. ☐ Feedlo	1. Domestic:       5. ☐ Public Water Supply: well ID							10.				
Was a chemical/bacteriological sample submitted to KDHE?  Yes  No If yes, date sample was submitted:												
Was a chemical bacter to logical sample submitted to KDTE! [188 ] No 11 yes, date sample was submitted:												
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded												
Casing diameter												
Casing height above land surface												
TYPE OF SCREEN OR PERFORATION MATERIAL:												
☐ Steel ☐ Stainless Steel ☐ Fiberglass ☐ PVC ☐ Other (Specify)												
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)												
SCREEN OR PERFORATION OPENINGS ARE:  Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify)												
		☐ Mill Slot ☐ Key Pund		uze Wrapped	] Tore	cn Cut LL	Villed Holes None (Open H	ا لــا (مامة	Other (Specify)		***********	
					J Daw	ft From	ft ff	0	ft From	ft to	. 4	
SCREËN-PERFORATED INTERVALS: From												
Grout Interv	als: From	400 ft. t	0 0	. ft., From	ft	. to	ft., From		ft. to	ft.		
Nearest sou	rce of possib	ole contaminat	ion:				-					
☐ Septic			Lateral Line				Livestock Pe		☐ Insection			
Sewer	Lines ight Sewer L		Cess Pool Seepage Pit	☐ Sewage ☐ Feedya			Fuel Storage Fertilizer Sto		☐ Abando			
				□ reedya			rennzer su	orage	☐ Oil We	n/Gas wen	·	
				Distance from					ft.			
10 FROM	TO		LITHOLOG	SIC LOG		FROM			HO. LOG (cont.) or		IG INTERVALS	
0		Clay/Broker				79		Shal		72-176 SI		
26		Lime				87		Lime	e 17	'6-197 Lir		
30		Shale						Shal		97-202 SI		
38						134		Lime		02-217 Li		
41						135		Shal		17-400 S	hale	
49						145						
67						Notes: 4-400' bores with 1" HDPE & 6-300' bores with 1" HDPE.						
. The state							Total 17 Ton					
72   79   Lime   11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ■ constructed, □ reconstructed, or ■ plugged												
under my jurisdiction and was completed on (mo-day-year) .09/03/21												
Mail	l white copy al	long with a fee of	\$5.00 for each	h constructed well to:	Kansa	as Department	of Health and	Envir	onmon, Bureau of Wa	ater, GWTS	Section,	
				66612-1367. Mail on				one for	your records. Teleph			
visit us at nti	//www.kdnek	cs.gov/waterwell/	maex.ntml		K	<u> SA 82a-12</u>	14			Kevised	17/10/2015	