	WATER WELL RECOP		KSA 82a-1			
1 LOCATION OF WATER WELL:	Fraction		n Number	Township Number	Range Number	
County: DICKINSON			33	т 14 s	R 3 (19)	
Distance and direction from nearest town	or city street address of well if	located within city?			RW	
2 WATER WELL OWNER: ARM	= RS MIM (MEND	USDA CLC				
RR#, St. Address, Box # :	2100 0000000000	V. 2.1		Board of Agriculture.	Division of Water Resources	
City, State, ZIP Code : Navav	re, Kanspas	0		Application Number:		
3 LOCATE WELL'S LOCATION WITH 4		ELL. 95	ft. ELEVAT	TION:		
AN "X" IN SECTION BOX:	Depth(s) Groundwater Encounter	red 1	ft. 2		3	
WELL'S STATIC WATER LEVEL						
Est. Yield gpm: Well water was , , ft. after hours pumping gpm						
	Bore Hole Diameter 1.2 in. to					
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well						
-   ·   ·   ·	1 Domestic 3 Feedlo	t 6 Oil field water	r supply 🖒	Dewatering p 12	Other (Specify below)	
37   37	2 Irrigation 4 Industr	ial 7 Lawn and gar	rden only 1	0 Monitoring well KECO	VERM WELL	
l i l v	Was a chemical/bacteriological sa	ample submitted to Dep	artment? Ye	s; If yes	s, mo/day/yr sample was sub-	
<u> </u>	nitted		Wat	er Well Disinfected? Yes	No X	
5 TYPE OF BLANK CASING USED:	5 Wrought iron	n 8 Concrete	tile	CASING JOINTS: Glue	ed Clamped	
1 Steel 3 RMP (SR)	6 Asbestos-Ce	ement 9 Other (s	pecify below	) Weld	ded	
2 PVC 4 ABS	7 Fiberglass	<i>A</i> ······	سنخض	Thre	aded	
Blank casing diameter 8in. to 4 ft., Diain. to 15 ft., Dia ft.						
Casing height above land surface Din., weight						
TYPE OF SCREEN OR PERFORATION	MATERIAL:	<b>∂</b> •vc		10 Asbestos-cem		
1 Steel 3 Stainless	steel 5 Fiberglass	8 RMP	(SR)	11 Other (specify	)	
2 Brass 4 Galvanized	d steel 6 Concrete tile	9 ABS		12 None used (o	pen hole)	
SCREEN OR PERFORATION OPENING	S ARE: 5	Gauzed wrapped		8 Saw cut	11 None (open hole)	
1 Continuous slot (3) Mill	slot 6	Wire wrapped		9 Drilled holes		
2 Louvered shutter 4 Key punched 7 Torch cut 6 10 Other (specify)						
SCREEN-PERFORATED INTERVALS: Fromft. toft., From						
ا ft. to ft. from ft. from ft. ft. from ft. ft. from ft. ft. ft. ft. ft.						
GRAVEL PACK INTERVALS: From						
	From f	t. to	ft., From	n ft.	to ft.	
6 GROUT MATERIAL: 1 Neat cement (2) Cement grout (2) Bentonite (3) Bentonite (4) 4 Other						
Grout Intervals: From						
What is the nearest source of possible co	ontamination:		10 Livesto	ock pens 14 A	Abandoned water well	
1 Septic tank 4 Lateral	lines 7 Pit pr	ivy	11 Fuel s	torage 15 (	Dil well/Gas well	
2 Sewer lines 5 Cess p	ool 8 Sewa	ge lagoon	12 Fertiliz	er storage 16 (	Other (specify below)	
3 Watertight sewer lines 6 Seepag	ge pit 9 Feedy	yard	13 Insecti	cide storage		
Direction from well? WKNOWN			How man	y feet?		
FROM TO	LITHOLOGIC LOG	FROM	то	PLUGGING	INTERVALS	
	lanz d. Ls			V		
64 75 LS & Clau	ystorie.					
	J					
					MALA	
				15,18	A CONTRACTOR OF THE PARTY OF TH	
				197	PG 15 14 15 15 1	
				16/5	PG ISIN EVOL	
				- \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	8 . 151	
				Q.	W/ 13	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was						
completed on (mo/day/year)						
Water Well Contractor's License No	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	ater Well Record was			-94	
	augne, INC.		by (signatu	- /\/\.\.\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	totaline Ce	
INSTRUCTIONS: Use typewriter or ball point per	0 (	early. Please fill in blanks, und			copies to Kansas Department	
of Health and Environment Bureau of Water To						