111004	ION OF W	ATER WELL:		WELL RECORD	Pomive			Alumah		Number -
County:		MICK WELL:	Fraction	MIND 44	CIE	Section Number			I -	Number
			NE 1/4	NE 14	SE 1/4	27	<u>T 14</u>	S	R 3	(E)\/
		on from nearest town		ddress of well if lo	cated within	city?				
		nial Road, Salin								
2 WATER	R WELL O	WNER: L & S Co	nstruction C	ompany						
		x# : 2141 Cen		7			Board of Ad	riculture, Divis	ion of Water	Pesourcos
City, State,			ansas 67401				Application		SIOTI OF VVAICE	resources
									10.0=	
MITHA	N "X" IN S			MPLETED WELL .						
_		N D	epth(s) Groundy	vater Encountered	i 1	ft	. 2	ft. :	3	ft.
⊼ Γ			ELL'S STATIC	WATER LEVEL .	13.6	. ft. below land s	urface measure	d on mo/dav/v	r 2/13	/2008
1	1	1		test data: Well w						
	- NW	NE		gpm: Well w						
0	1									
<u>≅</u> w				er 8 in.						
- ''	1	X	VELL WATER TO	D BE USED AS:	5 Public w	ater supply	8 Air condition	ning 11 l	njection well	
	i		1 Domestic	3 Feedlot	6 Oil field	water supply	9 Dewatering	12 (Other (Speci	fy below)
	SW	\$E	2 Irrigation	4 Industrial	7 Lawn an	d garden only	10 Monitoring v			
1	1	l i I I w	0	pacteriological sar						
Y L	i	, ,	ubmitted	Jaotoriologicai sai	ripic odbinia		ater Well Disinfe			√ Vas
1		3								_ ′
5 TYPE O	OF BLANK	CASING USED:	!	Wrought iron	8 Co	oncrete tile	CASING .	JOINTS: Glued	l Cla	mped
1 Ste	eel	3 RMP (SR)	•	Asbestos-Ceme	ent 9 Ot	her (specify bek	ow)	Welde	ed	
2 PV	/C	4 ABS	7	Fiberglass				Threa	ided. 🗸	
		r i		•						
		and surface		n., weight						1.40
TYPE OF S	SCREEN C	R PERFORATION N	MATERIAL			PVC	10 A	Asbestos-ceme	ent	
1 Ste	eel	3 Stainless st	teel 5	Fiberglass	8	RMP (SR)	11, 0	Other (specify)		
2 Bra	ass	4 Galvanized	steel 6	Concrete tile	9	ABS	12 N	ione used (ope	en hole)	
SCREEN C	R PERFO	RATION OPENINGS	ARE:	5 Ga	uzed wrappe	ad	8 Saw cut	(11 None (o	nen hole)
	ontinuous s				re wrapped		9 Drilled hole	_	11 None (o	pen noie)
	uvered shu		punched		rch cut		10 Other (spec			
SCREEN-P	PERFORAT	ED INTERVALS:	From	10 ft. to)ft., Fr	om	ft.	to	ft.
			From	ft. to		ft., Fr	om	ft.	to	ft.
GF	RAVEL PA	CK INTERVALS:	From	.8 ft. to		ft., Fr	om	ft.	to	ft.
				ft. to						
- COOLE	***									
GROUT	MATERIA	L: 1 Neat cer	ment 2	Cement grout	, (3)B	entonite 4	Other Concre	ete		
Grout Interv	vals: From	n	. to	ft., From	1	ft. to 8	ft., From		ft. to	ft.
What is the	nearest s	ource of possible co	ontamination:				stock pens		andoned wa	
1 Septio	c tank -	4 Lateral	lines	7 Pit privy			storage	15 Oi	l well/Gas we	ır
	r lines		ool		agoon		lizer storage		her (specify	
		r lines 6 Seepag					_		•	,
	٠	illes o Seepag	e pit	9 Feedyard	,		cticide storage	• • • • • •		
Direction from						How ma	<u> </u>			
FROM	TO		LITHOLOGIC LO	OG	FROM	/ TO		PLUGGING IN	TERVALS	
0	0.5	Gravel fill,				1 1				
0.5	2	Clay, silty, plast	tic. moist, no	odor, Black						
2		Gravel fill w/bro			-					
						 				
3		Clay, plastic, no							· · · · · · · · · · · · · · · · · · ·	
11.5	16	Silt, v. clayey, m	ioist, no odor	, Lt. Brown						
16	20	Silt, clayey to sl.	sandy, moist	Brown						
									·	
										
					+	-				
	-									
						-				
						I	MW3R , Tag # 0	042457 , Flush	mount	
						I	Project Name: L	and S Building	g Contractor	s - Monitorin
							GeoCore # 323,		W	
1001	OTODO	D I ANDOMA TESTS	OFFICE							
		R LANDOWNER'S								
and was cor	mpleted on	(mo/day/year)		2/13/2008		and this re	ecord is true to	the best of my	knowledge a	nd belief.
(ansas Wa	ter Well Co	ontractor's License	No	527	This Water V				2/27/2	
nder the bu							. / /			
						<u> </u>	, , ,			
INSTRUC	CTIONS: Use	me of typewriter or ball point p and Environment, Bureau	en PLEASE PRES	Core, Inc. SS FIRMLY and PRIN Kansas 66620-0001.	<u>7</u> clearly. Pleas Telephone: 913-	by (signa se fill in blanks, unde 296-5545. Send one	dine or circle the co	ment answers Se	end top three co	pies to Kansas