

1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SW 1/4 Section Number 24 Township Number T 14 S Range Number R 7 E
 County: Dickinson

Distance and direction from nearest town or city street address of well if located within city?
3 W Woodbine

2 WATER WELL OWNER: Max Stroda
 RR#, St. Address, Box # : 1608 900 Ave
 City, State, ZIP Code : Hope, KS, 67451
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N	
-NW-	-NE-
W	E
-SW-	-SE-
S	

X is in the SW corner.

4 DEPTH OF COMPLETED WELL 105 ft. ELEVATION: 95 ft.
 Depth(s) Groundwater Encountered 60 ft. 2 95 ft. 3 105 ft.
 WELL'S STATIC WATER LEVEL 60 ft. below land surface measured on mo/day/yr. 1-6-03
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 25 gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 1 Domestic 1 3 Feedlot 1 6 Oil field water supply 1 9 Dewatering 1 12 Other (Specify below)
 2 Irrigation 1 4 Industrial 1 7 Domestic (lawn & garden) 1 10 Monitoring well 1
 5 Public water supply 1 8 Air conditioning 1 11 Injection well 1
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 2 3 RMP (SR) 2 5 Wrought iron 2 8 Concrete tile 2 CASING JOINTS: Glued X Clamped
 2 PVC 2 4 ABS 2 6 Asbestos-Cement 2 9 Other (specify below) 2 Welded
 7 Fiberglass 2 Threaded
 Blank casing diameter 5 in. to 8.5 ft. Dia in. to ft. Dia in. to ft.
 Casing height above land surface 24 in., weight 12.2 lbs./ft. Wall thickness or gauge No. 214
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 7 3 Stainless Steel 7 5 Fiberglass 7 8 RMP (SR) 7 10 Asbestos-Cement 7
 2 Brass 7 4 Galvanized Steel 7 6 Concrete tile 7 9 ABS 7 12 None used (open hole) 7
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 5 3 Mill slot 5 5 Guazed wrapped 5 8 Saw cut 5 11 None (open hole) 5
 2 Louvered shutter 5 4 Key punched 5 6 Wire wrapped 5 9 Drilled holes 5
 7 Torch cut 5 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 25 ft. to 105 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 105 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 20 2 Cement grout 20 3 Bentonite 20 4 Other
 Grout intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 1 4 Lateral lines 1 7 Pit privy 1 10 Livestock pens 1 14 Abandoned water well 1
 2 Sewer lines 1 5 Cess pool 1 8 Sewage lagoon 1 11 Fuel storage 1 15 Oil well/Gas well 1
 3 Watertight sewer lines 1 6 Seepage pit 1 9 Feedyard 1 12 Fertilizer storage 1 16 Other (specify below) 1
 13 Insecticide storage 1
 Direction from well? In pasture for Cattle How many feet? None within 1/2 mi

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Clay			
4	32	lime mixed shale			
32	40	Blue shale			
40	55	yellow shale			
55	72	Red "			
72	95	lime mixed shale			
95		Water			
95	105	Gray shale/Fort Riley			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-6-03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 180 This Water Well Record was completed on (mo/day/yr) 1-12-03 under the business name of Backhus Drilling by (signature) Paul H. Backhus