


1 LOCATION OF WATER WELL: Fraction NE 1/4 SW 1/4 SW 1/4 Section Number 12 Township Number T 14 S Range Number R 6 E
 County: Morris

Distance and direction from nearest town or city street address of well if located within city? North of White City 3 1/4 miles on 2100 Ave 1/4 mile east

2 WATER WELL OWNER: Larry G. Nelson
 RR#, St. Address, Box #: P.O. Box 972
 City, State, ZIP Code: Junction City, KS, 66441
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 140 ft. ELEVATION:
 Depth(s) Groundwater Encountered: 1. 102 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 95 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield: 20 gpm; Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 8 in. to 140 ft., and in. to ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes. No. ; If yes, mo/day/yrs sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 Brass 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 3 Stainless steel 7 Fiberglass Threaded
 Blank casing diameter: in. to 120 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface: 3 in., weight 52.40 lbs./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes
 SCREEN-PERFORATED INTERVALS: From: 120 ft. to 140 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From: 25 ft. to 140 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From: 0 ft. to 25 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Top Soil	113	140	Limestone
1	3	Brown Clay			
3	5	Limestone			
5	8	Yellow Shale			
8	21	Brown Shale			
21	24	Limestone			
24	48	Brown Shale			
48	55	Limestone			
55	69	Yellow Shale			
69	84	Limestone			
84	95	Brown Shale			
95	102	Gray Shale			
102	105	Limestone			
105	113	Gray Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/3/2002 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 4513 This Water Well Record was completed on (mo/day/yr) 6/13/2002 under the business name of Haldeman Well Drilling by (signature) Larry G. Nelson