

MW9

WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No.

1 LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 NW 1/4 Section Number 35 Township Number T 14 Range Number R 6

Distance and direction from nearest town or city street address of well if located within city? Adolph + Mackenzie, White City Kansas 66872

2 WATER WELL OWNER: Dwight Fuel Service RR#, St. Address, Box #: P.O. Box 98 City, State, ZIP Code: Dwight Kansas 66847. Board of Agriculture, Division of Water Resources Application Number: 1469.80

3 LOCATE WELL'S LOCATION WITH AN 'X' IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the NW section] 4 DEPTH OF COMPLETED WELL: 110 ft. ELEVATION: 1469.80. Depth(s) Groundwater Encountered: 89 ft. WELL'S STATIC WATER LEVEL: 88.83 ft. below land surface measured on mo/day/yr: 03/25/02. Pump test data: Well water was ... ft. after ... hours pumping ... gpm. Est. Yield ... gpm: Well water was ... ft. after ... hours pumping ... gpm. Bore Hole Diameter: 8.25 in. to 110 ft., and ... in. to ... ft. WELL WATER TO BE USED AS: 5 Public water supply, 8 Air conditioning, 11 Injection well, 1 Domestic, 3 Feedlot, 6 Oil field water supply, 9 Dewatering, 12 Other (Specify below), 2 Irrigation, 4 Industrial, 7 Domestic (lawn & garden), 10 Monitoring well. Was a chemical/bacteriological sample submitted to Department? Yes. [No] X; If yes, mo/day/yrs sample was submitted. Water Well Disinfected? Yes [No] X

5 TYPE OF BLANK CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below), CASING JOINTS: Glued, Clamped, Welded, Threaded. PVC. Blank casing diameter: 10-7.00 in. to 70 ft., Dia. in. to ... ft., Dia. in. to ... ft. Casing height above land surface: 5.52 in., weight 0.8 lbs./ft. Wall thickness or gauge No. SCH 40. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless steel, 4 Galvanized steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RMP (SR), 9 ABS, 10 Asbestos-cement, 11 Other (specify), 12 None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Gauzed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw cut, 9 Drilled holes, 10 Other (specify), 11 None (open hole). SCREEN-PERFORATED INTERVALS: From 70 ft. to 110 ft., From ... ft. to ... ft., From ... ft. to ... ft. GRAVEL PACK INTERVALS: From 64 ft. to 110 ft., From ... ft. to ... ft., From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 1 ft. to 46 ft., From ... ft. to ... ft., From ... ft. to ... ft. What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer storage, 13 Insecticide storage, 14 Abandoned water well, 15 Oil well/Gas well, 16 Other (specify below) LUST SITE. Direction from well? How many feet?

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows include: 0' 2' Topsoil, 2' 10' Clay, brown, silty, dense. High plasticity, dry, no odor, 10' 14' Limestone - yellow, 14' 30' Shale - yellow, 30' 35' Limestone - gray, 35' 42' Shale - gray, 42' 46' Limestone - gray, 46' 69' Shale - reddish brown, 69' 110' Limestone - green, @ 95 Fractures

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 03/13/02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 594 This Water Well Record was completed on (mo/day/yr) 05/2/02 under the business name of Coranco Great Plains Inc. by (signature) [Signature]