

1 LOCATION OF WATER WELL: County: MORRIS		Fraction SE 1/4 SE 1/4 SE 1/4	Section Number 12	Township Number T 14 S 6	Range Number R 7 E/W
Distance and direction from nearest town or city street address of well if located within city? 7TH & MAIN DWIGHT KS					
2 WATER WELL OWNER: JIM KIRKEMIIDE					
RR#, St. Address, Box # : 7TH & MAIN DWIGHT KS 66849			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code :			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 31.5 ft. ELEVATION: 2.5 ft.			
		Depth(s) Groundwater Encountered 1. 13 ft. 2. 2.5 ft. 3. - ft.			
		WELL'S STATIC WATER LEVEL NA ft. below land surface measured on mo/day/yr -			
		Pump test data: Well water was NA ft. after - hours pumping - gpm			
		Est. Yield NA gpm: Well water was - ft. after - hours pumping - gpm			
		Bore Hole Diameter: 7.25 in. to 31.5 ft., and - in. to - ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes - No X ; If yes, mo/day/yr sample was submitted -					
Water Well Disinfected? Yes - No X					
5 TYPE OF BLANK CASING USED: NA					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued - Clamped - 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded - 7 Fiberglass Threaded -					
Blank casing diameter NA in. to - ft., Dia - in. to - ft., Dia - in. to - ft.					
Casing height above land surface NA in., weight - lbs./ft. Wall thickness or gauge No. -					
TYPE OF SCREEN OR PERFORATION MATERIAL: NA					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) - 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: NA					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) -					
SCREEN-PERFORATED INTERVALS: From - ft. to - ft., From - ft. to - ft., From - ft. to - ft.					
SAND GRAVEL PACK INTERVALS: From 13 ft. to 31.5 ft., From - ft. to - ft., From - ft. to - ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other BENTONITE GROUT					
Grout Intervals: From 9.5 ft. to 13 ft., From 4 ft. to 9.5 ft., From 9.5 ft. to 4 ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) CONTAMINATED SITE					
Direction from well? - How many feet? -					
FROM		TO		LITHOLOGIC LOG	
FROM		TO		PLUGGING INTERVALS	
0		3		TOP SOIL	
3		14		SILTY CLAY	
14		17.5		L.S.	
17.5		20.5		SILTY CLAY - YELLOW BRN	
20.5		25		L.S.	
25		27.5		SILTY CLAY - L.S. GRAVEL	
27.5		29		L.S. - CHERT	
29		31.5		SILTY CLAY / COARSE L.S. - GRVL	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 06-21-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 07-17-93 under the business name of EBBERTS DRILLING by (signature) <i>Arjan Ebbert</i>					