4 LOCATI	ON OF WATE	B WELL.	Fraction		WELL RECO	JRD For		tion Numb		Towns	hip Num	ber	Rand	ge Number	
County:		orris			SE ½	SE		12	1		14		R	´ _	E
Distance ar	nd direction fro		wn or city stre	eet addr	ess of well it	located wi	thin city?						•		
					7 [™] & Mair	Street,	Dwight, I	Cansas							_
2 WATER	WELL OWNE	R: Roge	r Parker						_						
RR#, St. Ad	idress, Box#	P.O. E	30X 98	0.40									ision of Wa	ater Resourc	es
City, State,	ZIP Code WELL'S LO	CATON WITH	11, NO 00	049						Аррисац	ion Num	ber:			-
3 AN "X" I	N SECTION E	BOX:	DEPTH	OF CO	MPLETED	NELL	35	ft. E	LEVATION	ON:					
			Depth(s) G	roundw	ater Encoun	tered 11.5			ft. 2			ft.	3		Ft.
	N		WELL'S ST	TATIC V	VATER LEV	EL !	NA ft.	below lar	nd surfac	ce meas	ured on	mo/day/	/yr		5
+ Γ	i			Pump t	est data: \	Vell water	was		Ft. aft	er		hours p	oumping	G _l	om c
1 1_	\\\\/	NE	Est. Yield		Gpm: \	Nell water	was		Ft. aft	er		Hours	pumping	G _l	om j
	i	i	Bore Hole I	Diamete	r 8.625	In. to	3	5	ft. a	nd		ir	n. to		Ft.
∰ W -	-		E WELL WAT	TER TO mestic	BE USED A 3 Feed lot	AS: 5 Pu 6 Oil	blic water s field water	supply	(B Airco Dewa	inditionir Iterina	ig 1 1	1 Injection 2 Other (S	n well Specify belov	v) -
1			2 Irric	ation	4 Industria	ıl 7 La	wn and gar	den (dome	estic)	10 Mon	itorina w	ell	M۱	N-29	
 -	sw	SE X	1		acteriologica										S
↓ 1			Submitted	moanbe	cteriologica	sample se	Diffict to							No X	
5 TYPE O	F BLANK ČAS	SING USED	Cabinitada		5 Wrought	Iron	8 Concr						d		
1 Ste		3 RMP	(SR)		6 Asbesto							Weld			
2 PV		4 ABS	(=- · ·)		7 Fibergla				,				aded	X	
-					Ft.										
Blank casin	g diameter	2	in. to	20	Dia		ln.	to	ft.	, Dia			in. to		ft.
Casing heig	tht above land	I surface	FLUSH		., weight	SC									
	CREEN OR F				5 50			PVC							ł
1 Ste 2 Bra			less steel anized steel		6 Concrete			RMP (SF ABS	()	11	Other (specity) sed (on	en hole)		-
	ass R PERFORA						d wrapped		8					(open hole)	
	ntinuous slot		Mill slot			6 Wire w	rapped		9	Drilled	holes			, ,	
2 Lo	uvered shutter	r 4	Key punche	ed		7 Torch	cut		10	Other ((specify)			
SCREEN-P	ERFORATED	INTERVALS	S: From	2	20 ft	to	35	ft	t. From			ft. t	0		ft.
			From		ft	to		f	t. From			ft. t	0		Ft.
SA	ND PACK INT	ERVALS:	From	1	1 8 ft	to	35	fi	t. From			ft. t	0		Ft.
			From			to		f	t. From			ft. t	0		Ft.
6 GROUT	MATERIAL:	1 Neat	cement	2 (t		ntonite	4 0	ther					
Grout Inten	als From3	0	ft to	2	Ft. From2	2	Ft. to								
	nearest source								estock				andoned w		
	ptic tank	·	4 Lateral		7	Pit privy			el stora	~~		15 Oil	well/ Gas	well	
2 Se	wer lines		5 Cess po	ool	8	Sewage I	agoon	12 Fe	rtilizer s			16 Oth	ner (specify	below)	
3 Wa	atertight sewer	lines	6 Seepag	e pit	9	Feedyard		13 Ins	secticide	storage	е	Co	ntamina	ated Site	
Direction fro	m well?						,	How ma	ny feet?	?					
FROM	TO	CODE			GIC LOG		FROM	ТО			PLUG	GING IN	TERVALS	3	
0	2		ay, hard,				ļ								
2	5.5		lay, silty, ay, silty,			MD.									
5.5 12	12 35	CI	ay, silty,	very s	stiff velle	WII			-						\dashv
35	TD	Er	nd of Bore	ehole	Jenn, you										
								<u> </u>							\neg
															_
								-							
								-							-
									-						
	ACTOR'S OR					er well was						-			- 1
	on (mo/day/yr			03/03/									•	lief. Kansas	
	Contractor's L				585			Vater Well						03/31/09	
under the bu	usiness name UCTIONS: Ple	of	ASSO	ciate	d Environ	nmental	, Inc.	as Donarda	By (sig	nature)	Brac	ney J	Johnso	n Na Tanaha	_
Kancac	UCTIONS: PIE	case III III DIANI Telephone: 91	s and circle th	Send one	to MATER I	MELL OWN	pics to Kans FR and retai	n one for w	nent of M	eaith and	J Environ	ment ee	reaujoyvva	er, Topeka,	